

# M 4300



The new 4300 MARK M is a power of four channels capable of delivering up to 1600W in total. Each channel has in the back with an XLR input and a potentiometer on the front to adjust the volume.

The M 4300 has the ability to be configured in 3 modes: stereo, parallel and bridge, thus adapting to any installation.

Its low THD, all the protections and the light weight makes it a versatile and portable stage.

## Especificaciones:

**TA 1 kHz THD <0.5%:**

**Estereo: 8/4Ω: 4x300W / 4x400W**

**Paralel: 8Ω: 2x300W**

**Bridge: 8Ω: 4x600W**

**Frecuency response: 20Hz-20kHz**

**Input sensibility: 1V**

**S/N Relation: 100 dBA**

**THD: 0.1%**

**(SMPTE): 0.1%**

**Input impedance: 20 kHz (Balanced) 10kHz (Unbalanced)**

**(5Hz-1kHz) Damping Factor: >200**

**SLEW RATE: 20V/us**

**Connections: XLR (Input) - BINDING SPOT (Output)**

**Protections: Soft Start, DC, VHF, AC, Shortcircuit, Limiter, Temperature**

**Power Supply: 115V/235V AC, 50/60Hz**

**Dimensions: 483 × 280 × 44mm**

**Weight: 5 Kg**