

Lighting

09/10



WORK is a brand of **EQUIPSON**[®] S.A



Since 1995, **Equipson S.A.** offers an exclusive range of professional audio and lighting products, truss system and accessories for the entertainment industry.

With its leading brand **WORK**[®], the company aims to offer innovative and competitive products, with great efforts of our R&D department in designing highly technological devices. A special care is taken in electronic design and hardware packaging. **WORK**[®] products have been designed to meet the real needs of the industry, by offering an adequate answer for almost any installations and touring applications.

Every year, the company takes part to the main international trade shows. **WORK**[®] products are of course distributed over the 5 continents.



Facade of Equipson S.A.

Dear friend,

We are very proud to send you this new 2009/10 catalogue!

This publication is very special for us, as it represents years of efforts dedicated to people in the trade with the will to offer an exclusive range of professional audio and lighting products.

As you know, we have been strongly investing on our R&D department over the last years, devoting a full plant for **WORK**® product development and innovation. Today it bears fruits and so you will discover in this new catalogue exclusive products that perfectly meet professional needs. As a recognition of this strategy of research and technological development, **WORK**® has received the stamps of IMPIVA: the European union recognizes company's contribution to its sector.

Regarding quality process, there is a constant upgrade of existing products, taking into account user experiences and commentaries. We take care of the overall design of products, from internal components to finishing. A complete revision of products is done when a new production starts.

For maximum convenience, **WORK**® products have divided in four catalogues:

- **Audio catalogue:** We present full solutions for any of your audio installations, by offering an adequate answer for almost any installations (airports, museums, auditoriums, theatres, bars, etc.) and touring applications.
- **Lighting catalogue:** Lighting designers and professional VJs will take advantage our product selection, with an impressive range of LED fixtures and controllers.
- **Towers and truss catalogue:** Even if quality and reliability of **WORK**® lifting towers have been proved over the years, we still develop new models and improve existing ones. We ensure that they all achieve the strictest international security norms.
- **Accessories catalogue:** We offer all the accessories required for your audio/lighting installations. We have extended our selection to offer accessories suitable with the newest technologies.

Every years **WORK**® audio and lighting products are shown at all the important international trade shows (PLASA Show, Prolight+sound, Afial, Infocomm, etc.). This is the best opportunity to meet our engineers and ask anything you want about new products. We will be proud to help you in any of your projects.

Best regards,

José Vila





lighting

lighting



- 6_ STAGE DMX CONTROLLERS.
- 20_ ARCHITECTURAL DMX CONTROLLERS.
- 26_ DIMMERS.
- 37_ CONTROLLERS WITH DIMMER.
- 42_ DMX RECORDERS.
- 44_ DMX TOOLS.
- 54_ VOLTAGE REGULATORS.
- 58_ POWER DISTRIBUTORS.
- 67_ AUXILIARY VIDEO DEVICES.
- 68_ LED FIXTURES.



LightON 3

LightON 5

DMX consoles

NEW



LightON 3



LightON 5

Connection example of a VGA monitor and LightON consoles.
(MONITOR NOT INCLUDED).

Lighting consoles LightON

LightON series is composed of two consoles of 512 DMX channels designed for conventional lighting, moving lights and LEDs. Their main difference is the number of faders they feature (24 for **LightON 3** and 48 for **LightON 5**).

Operating modes.

Both units provide 6 operating modes: Single scene, Double scene, Sub Master, Moving Light, Led and Memory.

First two modes allow the selection of scenes and their edition (time fade). These scenes are triggered with A and B faders and sent to their respective outputs.

Using the Sub Master mode, user gets access to any of the 1152 programmable scenes (48 scenes x 24 pages) that can be triggered with adjustable fade time. Crossfade is available between two shows. Moving Light mode allows the full control of moving lights and scanners. Many fixtures can be controlled together. LED mode is dedicated to RGBA LED fixtures control. It provides the effects, groups and patches for an easy control of units.

The many scenes available and their easy creation increase possibilities of **LightON consoles**, whatever the operating mode selected.

Enjoy the advantages of a visual console.

LightON consoles have been designed to provide a visual interface. Included LCD display gives users clear information about the different devices. Its back-lighted buttons (by RGB LED) change their colour depending on the state of the console.

LightON consoles also feature an optional **VGA monitor output**. Most demanding users who need additional information can now connect their console to an external monitor and get all the details they want.

Advanced communication.

Thanks to the USB port, user can download/upload data and upgrade internal software. The Ethernet connector allows the connection with other fixtures integrated in an **ArtNet** network.



60 x 128 dot LCD display. Back-lighted buttons change their colour depending on state and function. Predetermined channels for LED fixtures control (RGBA) and control for Movie Lights (PAN/TILT, etc).




VGA card (optional).



ArtNet connector for LightON integration in Ethernet network. USB interface for internal software upgrading. VGA connector for monitor connection allowing visualization of channel states (MONITOR NOT INCLUDED).

light ON



LightON 5



LightON 3

REAR PANELS

LightON 5



LightON 3



FEATURES

- Multi purpose lighting consoles: conventional lighting, moving heads and LED fixtures.
- 60x 128 dot LCD display with contrast control.
- USB port for download/upload data and upgrade internal software.
- ArtNet port for a fast communication with compatible devices.
- 6 operating modes: Single scene, Double scene, Sub Master, Moving Light, LED and Memory.
- 24 faders (**LightON 3**) or 48 faders (**LightON 5**) for conventional lighting, moving heads and LED fixtures.
- 1152 programmable scenes (48 scenes x 24 pages) in Sub Master mode for conventional lighting.
- Control of 8 moving lights (**LightON 3**) or 24 moving lights (**LightON 5**), with up to 40 channels each. 20 playbacks of 99 steps each, using Moving Light mode.
- Control of 8 RGBA LED fixtures (**LightON 3**) or 24 RGBA LED fixtures (**LightON 5**). 20 playbacks of 99 steps each, using LED mode.
- 12 effects with programmable fade time and speed (up to 99 steps for each effect).
- Memory mode to mix Sub master, Moving Light and LED operating modes.
- Grand Master fader to control the overall output.
- A and B faders with separate output that allow crossfade between them.
- Blackout function.
- Back-lighted buttons that change their colour depending on their state.
- Port for an optional VGA card (800x600 pixels).
- Main supply: DC 9-12 V, 2 A (power supply unit included).
- Dimensions (WxHxD):
 - LightON 3:** 483 x 265 x 66 mm.
 - LightON 5:** 718 x 265 x 66 mm.




GALAXY DMX

DMX console



Slot for 32MB Compact Flash cards (play and record functions).



Grand Master for all fixtures.



Joystick for PAN/TILT control from 8 to 16 bits (selectable).

GALAXY DMX has been designed to combine in a same console all the controllers required for lighting control. It features different sections: for conventional lighting control, for moving head control and for independent flash and DMX fog machines.

Intuitive interface.

Interface for creation and edition is very intuitive and ensures the perfect control of all the parameters. Two LCD displays provide a fast visualization of the state of the fixtures and an easy access to the different menus.


Programs and libraries can be edited as files and transferred or uploaded by the console, using the RS232 port communication or the slot for a 32 MB compact flash card.

Control capacity.

Internal storage capacity of the console is very useful, as it allows the creation of many programs for spots and robots control. Actually, it creates up to 48 programs for conventional lighting, 48 for robots and other 20 for DMX flashes. With 512 DMX channels available, **GALAXY DMX** can control 16 robots, 24 conventional lighting fixtures, 4 DMX flashes and a DMX fog machine.

FEATURES

- 512 DMX channels (16 robots, 24 conventional lighting fixtures, 4 DMX flashes and a DMX fog machine).
- 48 programs for fixtures (48 steps per program).
- 48 programs for robots (48 steps per program).
- 20 programs for flashes.
- Internal library configurable for 256 robots.
- Joystick for PAN/TILT movements.
- RS232 communication port and slot for 32MB compact flash card.
- MIDI interface.
- Blackout function.
- Main supply: AC 240/120 V. (power supply unit included).
- Dimensions (WxHxD): 626 x 384 x 103 mm.
- Weight: 14 kg.





NEMESIS 136 DMX

DMX console

This hybrid console (conventional lights and robots) with reduced dimensions is a great solution for small/medium night clubs and mobile DJs.

Control capacity.

With 136 DMX channels, **NEMESIS 136 DMX** ensures the full control of 8 robots (16 channels each) and features 8 exclusive channels for control and dimming of conventional lighting. Both controls have their own section. All the programs can be executed with speed time defined by the internal memory, speed fader, MIDI interface or even with audio synchronization system. For a better precision in PAN/TILT channel configuration, **NEMESIS 136 DMX** has an ergonomic joystick. The console provides fast access buttons to previously recorded scenes of robots and spots. Many robots can be controlled together for maximum convenience.

The LCD display gets access to real time information: it shows parameters and their current value.

Designed for mobile applications.

Internal memory of **NEMESIS 136 DMX** can store up to 96 programmable scenes for spots, 8 programs for robots and 6 for spots (up to 99 steps each). A slot for a 32 MB compact flash card allows storing and sending the information. Its rubber shock protection ensures that the console will not suffer any damage during transport and live shows. It can also be fixed to a 19" rack.



Control interface with LCD display.




Patch joystick for PAN/TILT movements.

FEATURES

- 136 DMX control channels.
- 8 robots, each one with up to 16 channels.
- 8 channels for conventional lighting.
- 96 programmable scenes for robots.
- 96 programmable scenes for spots.
- 8 programs for robots and other 6 for spots (with 99 steps each).
- 16/8 bit resolution for PAN/TILT movements.
- Ergonomic joystick for PAN/TILT control.
- Slot for 32 MB compact flash card.
- Connection for external foot switch and fog machine trigger.
- Blackout function.
- MIDI interface.
- Memory against current failures.
- Removable rubber shock protection.
- Main supply: DC 9-15 V, 600 mA. (power supply unit included).
- Dimensions (WxHxD): 495 x 188 x 88 mm.
- Weight: 5 kg.



Rubber side protections.





SCAN 1000 DMX

DMX console

2
consoles-in-one:
DMX and
MIDI



RACK SCAN
(optional).



Backup Memory stick (optional).



USB port and fog machine control.

SCAN 1000 DMX is very intuitive and provides the functions to create many different scenes. It controls up to 12 scanners (each one with 16 channels) for a total of 192 DMX channels.

The console features an internal programming capacity of 30 banks of 8 scenes each and 12 chases of 240 programmed steps. All these chases and scenes have can be automatically programmed, with parameters like speed or fade time. They are controlled by processor speed, by MIDI interface or even with audio synchronization system (it has an external connector and a microphone).

For a manual control of robots and scanners, PAN/TILT movements can be patched to the joystick of the console. This module can be switched for two Jog-wheels (one for each movement).

It provides a USB port for data transfer or even console backup. It is also useful to connect many **SCAN 1000 DMX** together and so send/receive data in DMX mode. In addition its 5V supply can be used to connect a LED Lamp.

FEATURES

- Console designed for intelligent lighting control.
- 192 DMX control channels.
- Control of 12 scanners with up to 16 channels each.
- Fader Speed and Fade time.
- 30 banks of memory, each one with 8 programmable scenes.
- 12 programmable chases (240 steps for each chase).
- Configurable PAN/TILT and Fade Time.
- MIDI control for banks, chases and blackout.
- Joystick for PAN/TILT movements.
- Connection for external foot switch and fog machine trigger.
- Internal microphone and Line connection for audio synchronization.
- RS232 and USB port to send/receive data.
- USB ports for lamp or memory stick connection.
- Main supply: DC 9-15V, 500 mA. (power supply unit included).
- Dimensions (WxHxD): 483 x 82 x 135 mm.
- Weight: 2.2 kg.

In this new version, **SCAN 1000 DMX** features an additional USB port on the rear panel to connect a PC and convert it into a MIDI console. In this configuration, it becomes possible to control any audio/lighting/video softwares that accept MIDI control: ArKaos Grand VJ, Simulight, Sunlite, Traktor and others softwares related to DJ, VJ and lighting which can be controlled by MIDI software.



Removable rubber
side protections.

REAR PANEL





SCAN 1216 DMX

DMX console



RACK SCAN (optional).

SCAN 1216 DMX is a compact lighting console for intelligent lighting like scanners or moving heads.

It features 192 DMX control channels that can manage up to 12 scanners and moving heads (16 channels each). These channels are integrated in two scenes of 8 channels accessible with a simple push button.

Control is not only manual, as **SCAN 1216 DMX** provides 30 banks of 8 programmable scenes (max. 240 programmable scenes) and other 6 chases per scene. Speed and fade time can be configured for any created program. The powerful programming function allows the addition of steps, the copy of scenes and scanner programming (that can be easily deleted).

SCAN 1216 DMX has two Jog-wheels that patch PAN and TILT channels for an intuitive control of lighting fixtures using these functions. Both channels are reversible.

All the programs stored in the console can be controlled with the speed control Jog-wheel, Tap Sync function, audio synchronization system (thanks to the internal microphone) or even MIDI function. The latter can activate 15 banks of scenes, 6 chases and the blackout function. Two **SCAN 1216 DMX** can be connected together to copy or exchange their respective programming banks and scenes.

Its rubber shock protection ensures that the console will not suffer any damage during transport and live shows. It can also be fixed to a 19" rack.

FEATURES

- Lighting console designed to control 192 DMX channels (12 robots of 16 channels).
- 30 banks of 8 programming scenes.
- 6 chases per scene.
- Jog-wheel for PAN/TILT functions (reversible).
- Copy of banks and scenes between consoles.
- Speed, audio, MIDI and Tap Sync synchronization.
- Blackout function.
- DMX polarity selector.
- Push button for fog machine trigger.
- Memory against current failures.
- Main supply: DC 9-12 V, 300 mA (power supply unit included).
- Dimensions (WxHxD): 483 x 132 x 73 mm.
- Weight: 2.5 kg.



Rubber side protections.

REAR PANEL





SCAN 812 DMX

DMX console



RACK SCAN (optional).

SCAN 812 DMX is a compact lighting console for intelligent lighting like scanners or moving heads. It features 192 DMX control channels that can manage 12 scanners and moving heads with 16 channels each. These channels are integrated in two scenes of 8 channels accessible from a simple push button.

SCAN 812 DMX provides 30 banks of 8 programmable scenes (max. 240 programmable scenes)

and other 6 chases per scene. Speed and fade time can be configured for any created program. The powerful programming function allows the addition of steps, the copy of scenes and the full programming of scanners (that can be easily deleted). A USB port is available to connect a lamp.

Its rubber shock protection ensures that the console will not suffer any damage during transport and live shows. It can also be fixed to a 19" rack.

FEATURES

- Lighting console designed to control 192 DMX channels (12 robots of 16 channels).
- 30 banks of 8 programming scenes.
- 6 chases per scene.
- Copy of banks and scenes between consoles.
- Speed, audio, MIDI and Tap Sync synchronization.
- Blackout function.
- Memory against current failures.
- Main supply: DC 9-12 V, 300 mA (power supply unit included).
- Dimensions (WxHxD): 483 x 132 x 73 mm.
- Weight: 2.5 kg.



Removable rubber side protections.

REAR PANEL





SCANPLAYER II DMX

DMX console

SCANPLAYER II DMX is a compact lighting console for intelligent lighting fixtures featuring 64 DMX channels (up to 8 robots of 8 channels each). Thanks to the ergonomic joystick and for maximum convenience, channels are patched to a unique control.

Up to 96 scenes and 4 programs can be programmed to patch robots and use parameters such as fade time, speed or Tap Sync (chase is executed using manual pulse).

Any data can be transferred or uploaded by the console, using the RS232 port communication or the slot for a 32 MB compact flash card.



Interface for scene creation and edition.
Ergonomic joystick to patch PAN/TILT channels.

FEATURES

- Lighting console designed to control 64 DMX channels (8 robots of 8 channels).
- 96 programming scenes.
- 16/8 bit resolution for PAN/TILT.
- Slot for a 32 MB compact flash card.
- RS232 port communication.
- Connection for fog machine trigger.
- Blackout function.
- Memory against current failures.
- Main supply: DC 9-15 V, 500 mA (power supply unit included).
- Dimensions (WxHxD): 360 x 193 x 74 mm.
- Weight: 2.2 kg.



Channel controls, Pages/Scenes/Mode selection.





STAGE 4824 DMX

DMX console



STAGE 4824 DMX is a conventional lighting console that features all the functions required for applications like theatres, studios and stages.


Its internal memory, with 48 programs and 4.600 steps, allows its use in almost any situation. 48 channels outputs can be divided in 2 x24 to create 2 different scenes and switch them with a crossfader movement. Its backup allows storing many configurations of scenes and chases for different events, and it is possible to get access to its memory and edit parameters. Many programs, scenes and chases can be edited at the same time and independently, providing a great range of effects with a small memory data base. Trigger of shows can be remotely programmed using MIDI.

Its memory against current failures ensures that the console will maintain the position of the show. Its rubber shock protection guarantees that it will not suffer any damage during transport and live shows.

FEATURES

- 48 DMX control channels for conventional lighting.
- 96 programs (4 pages of 24 programs).
- DMX address patchable for all channels.
- Flash switches for all channels.
- Fade time control: from 0 to 10 min.
- Memory against current failures.
- Speed, audio, MIDI and Tap Sync synchronization.
- Connection for external foot switch and fog machine trigger.
- Password to avoid any undesired external manipulations.
- 12 factory preset programs.
- Main supply: DC 12-20 V, 500 mA (power supply unit included).
- Dimensions (WxHxD): 712 x 111 x 85 mm.
- Weight: 7.2 kg.

RACK STAGE 15 (optional).



Reversed masters for preparations.



Fog machine control.

REAR PANEL





STAGE 2412 DMX

DMX console



RACK STAGE 10
(optional).

STAGE 2412 DMX is a conventional lighting console featuring 24 control channels that can be divided in 2 x12 to create 2 different scenes and switch them with a crossfader movement.

The latest software version includes a Patch function when each fader can be patched to any channel in the DMX universe.

Its internal memory, with 48 programs (36 + 12 factory) and 4.600 steps, allows its use in almost any situation. Its backup allows storing many configurations of scenes and chases for different events. It is possible to get access to its memory and edit parameters.

User can choose between many modes to trigger chases: Speed control, Audio mode, Standard Beat function or MIDI (in this case, each MIDI channel represents a channel of the console, so it is possible to transfer data from an external MIDI device).

Its memory against current failures ensures that the console will maintain the position of the show. Its rubber shock protection guarantees that it will not suffer any damage during transport and live shows. It can also be fixed to a 19" rack.

FEATURES


- 24 DMX control channels for conventional lighting.
- 96 programs (4 pages of 24 programs).
- DMX address patchable for all channels.
- Flashes switches for all channels.
- Fade time control: from 0 to 10 min.
- Memory against current failures.
- Speed, audio, MIDI and Tap Sync synchronization.
- Connection for external foot switch and fog machine trigger.
- Password to avoid any undesired external manipulations.
- 12 factory preset programs.
- Main supply: DC 12-20 V, 500 mA (power supply unit included).
- Dimensions (WxHxD): 530 x 330 x120 mm.



Rubber side protections.




Fog machine control.



Reversed masters for preparations.

REAR PANEL





STAGE 1624 DMX

DMX console



STAGE 1624 DMX is a conventional lighting console that features 16 control channels.

It provides 8 factory preset scenes easily accessible and other 16 configurable ones. Scenes can be faded to "0", just pushing the new program.


Most interesting features of **STAGE 1624 DMX** are its fast interface and intuitive use: with only one push button, user gets access to the program he wants. Each channel has its own flash switch to start channel and for a manual control. All the programs can be triggered with speed time defined by internal memory, speed fader, MIDI interface or even with audio synchronization system.

The LCD display gets access to real time information: it shows the current value and channel, being useful for scenes creation. Channel values can be visualized in percentage and absolute values (0-255). The console can be connected to a remote control unit to switch Off/On functions.



RACK STAGE 10
(optional)

REAR PANEL



FEATURES

- 16 DMX control channels for conventional lighting.
- 24 programs (16 programmable scenes + 8 factory programmed scenes).
- Flash switches for all channels.
- Memory against current failures.
- Speed, audio, MIDI and Tap Sync synchronization.
- Connection for external foot switch and fog machine trigger.
- DMX polarity selector.
- Password to avoid any undesired external manipulations.
- Connection for remote control (switch Off/On).
- Main supply: DC 12-20 V, 500 mA (power supply unit included).
- Dimensions (WxHxD): 483 x 222 x 85 mm.
- Weight: 4.4 kg.

STAGE 16 DMX

DMX console

This compact conventional lighting console is ideal for small stages and mobile shows.

Its internal memory provides 30 factory preset patterns and other 30 that can be edited by users. Each channel has a flash power switch for manual mode.

STAGE 16 DMX has many modes like LOOP function for scenes selection and their continuous triggering. CROSS function plays scenes using the minimum and maximum values of Master fader. It is possible to trigger scenes using the internal speed, audio, MIDI and Tap Sync synchronization.

The console can be connected to a remote control unit to switch off or switch on functions. These functions are also available on keyboard.



FEATURES

- 16 DMX control channels for conventional lighting.
- 30 factory preset programmed patterns + 30 programmable patterns (99 scenes per patterns).
- Speed, audio, MIDI and Tap Sync synchronization.
- Memory against current failures.
- Flash switches for all channels.
- DMX polarity selector.
- Main supply: DC 12-20 V, 500 mA (power supply unit included).
- Dimensions (WxHxD): 320 x 180 x 75 mm.
- Weight: 2.3 kg.



PROLIGHT 400 DMX

DMX chaser

This 4 channel chaser sends both analog (0-10V) and DMX signals.

It features 42 factory programmed scenes that can be triggered using audio source (RCA input + internal microphone) or a configured speed. It loops eight times a program and then starts the following one (for audio and speed modes). The additional trigger mode allows the creation of 32 chases that will be executed in the two previous modes.

With **PROLIGHT 400 DMX**, users can program fade time between scenes as well as the addition of flash and Stand By buttons.

FEATURES

- 4 channel chaser that sends both analog (0-10V) and DMX signals.
- 42 factory programmed scenes.
- Operating modes: Auto speed, Prog speed, Hold dimmer, Hold sound, Prog sound, Auto sound, Memory.
- Flash, Full-on, Blackout, and Tap Sync functions.
- Memory function with up to 32 steps.
- Main supply: DC 15-20 V, 400 mA. (power supply unit included).
- Dimensions (WxHxD): 483 x 132 x 50.5 mm.
- Weight: 2.3 kg.



L 16 DMX

DMX console

This DMX console with 16 faders and programmable DMX start address channel is very useful for test purposes and for simple applications.

L 16 DMX has a Master fader that controls maximum values of all the channels. Its LCD display indicates current channel value on percentage or absolute values (0-255), depending on the configuration of the MODE function.

REAR PANEL



FEATURES

- 16 DMX control channels for conventional lighting.
- Programmable DMX start address channel.
- Visualization of current channel value on percentage or absolute values (0-255).
- Main supply: DC 9 V, 100 mA. (power supply unit included).
- Dimensions (WxHxD): 483 x 132 x 80 mm.
- Weight: 2.3 kg.

This lighting console features 6 DMX channels and Master control.

Thanks to its compact design and mobility, small programs can be edited without having to use most sophisticated lighting consoles. It can also be used as a classic mixer.

L 6 DMX works with an external power supply unit or with a DC 9 V battery.



REAR PANEL



FEATURES

- 6 DMX control channels for conventional lighting.
- Main supply: DC 9 V, 100 mA. (power supply unit included) or DC 9 V battery (not included).
- Dimensions (WxHxD): 153 x 173 x 55 mm.
- Weight: 0.8 kg.

L 6 DMX

DMX console



AR 32

Advanced DMX controller/recorder system

ar32

**NEW
VERSION**



AR 32 C



AR PS1



Infrared port.



USB port.



Push buttons for chase speed adjustment.



Remote control.



Control software.

This useful architectural lighting recorder is composed of two devices: **AR PS1** and **AR 32 C** (with remote control).

It records your best shows.

AR 32 system is a DMX player/recorder that stores up to 32 shows coming from an external DMX console and plays them with a unique button.

Function of **AR PS1** is to receive DMX signals from external consoles and turns it into a compatible format. Information is sent to **AR 32 C** using the RJ45 interface.

It controls flash files with LED effects.

AR 32 system is an advanced control system that controls flash files (*.swf) and trigger them as LED effects, taking advantage of this technology.

Thanks to its USB port, **AR 32 C** can be connected to a PC with control software to control show parameters. LEDs on the front panel indicate when shows are stored.


New version includes 2 push buttons for a manual control of speed and chase triggering.

Ideal for pubs or any domestic use.

Portability and easy programming of **AR 32 system** convert it into a useful device that provides the adequate atmosphere to small and medium spaces like pubs. For maximum convenience, **AR 32** includes a remote control.


AR 32 as a DMX recorder

1º step




Creating shows with a DMX console.

2º step



Converting to AR 32 format.

3º step



Saving shows to keypad.

4º step



Ready to play.

TECHNICAL DATA	AR 32 C
Storage memory:	Up to 248 files / 128 MB.
Control method:	DMX, Manual and Timer (shows).
Ports:	RJ45 (main supply) infra-red (control).
Main supply:	DC 12 V.
Dimensions (WxHxD):	90 x 130 x 25 mm.

TECHNICAL DATA	AR PS1
Ports:	RJ45 (supply for AR 32 C).
Main supply:	DC 12 V.
Consumption:	500 mA.
Dimensions (WxHxD):	155 x 73 x 42 mm.

FEATURES

AR 32 C.

- Wall-mount / desktop system.
- USB port for PC communication.
- Flash (*.swf) to .SNC files converter.
- DMX to .SNC converter.
- Programmable shows and triggering time for each show.
- Up to 248 files and 128 MB storage memory to control DMX signal files.
- Up to 32 shows (8 per page) assigned to flash scenes.
- DMX control, Time trigger and Manual modes to playback shows.
- Included infra-red remote control.
- Keypad: 4 page buttons, 8 show buttons, Auto/Manual modes and OFF function.

AR PS1.

- Reads DMX signals coming from an external console.
- RJ45 interface and data exchange with AR 32 C.



AR RGB

DMX wall-mount controller

NEW



Remote control.

AR-RGB is a wall-mount controller that controls through DMX protocol the R, G and B information in the loaded devices. Control is very intuitive and easy, thanks to touch buttons that allow controlling each colour.


AR RGB includes 10 patterns to control fixtures, with parameters like fade time or speed that are controlled directly from the front panel. All these functions can be controlled by IR remote control.

FEATURES

AR RGB

- Wall-mount DMX controller.
- RGB control through DMX protocol.
- 10 RGB patterns.
- Built-in IR receiver and IR remote control included.

TECHNICAL DATA	AR-RGB
Main supply:	DC 12 V.
Connection:	RJ45.
Housing:	Polycarbonate.
Operating temperature:	-10° + 50°C.
Dimensions (WxHxD):	86 x 86 x 45 mm.
Weight:	200 g.



Installation with individual R,G,B control. Also AR-RGB includes 10 patterns for automatic control.

AR PS1



Optional device for the **AR** series for power and DMX supply with RJ45 cable (supply unit included).

AR-6 is a 6 channel DMX controller integrated in a ultra-small wall-mount interface, covering a lot of possibilities.

It can directly manage channels thanks to the 6 micro-faders and a master control. User can save up to 6 scenes and trigger them with the buttons placed on the right side.

In addition, it includes a IR receiver and a IR remote controller to manage all the functions remotely and trigger chases with the 6 scenes saved.

FEATURES

AR 6


- Wall-mount DMX controller.
- 6 micro faders for channels
- 1 micro fader for Master control
- 6 scenes of 6 DMX channels with Direct button access.
- IR receiver and remote control included
- Chases made by the 6 scenes can be triggered.
- Fit in a standard euro size electric box.

TECHNICAL DATA	AR-6
Main supply:	DC 12 V.
Connection:	RJ45.
Housing:	Polycarbonate.
Control :	6 DMX channels.
Operating temperature:	-10° + 50°C.
Dimensions (WxHxD):	86 x 86 x 45 mm.
Weight:	200 g.




NEW

Remote control.



AR-6 as conventional lights controller. It allows to manage a 6 DMX channels dimmer for six different zones.



Installation with 2 zones using AR-6. Its 6 DMX channels allows to control each RGB information.



HOMELED

DMX wall-mount controller

NEW




HOMELED is a 3 channel DMX controller all appropriate for RGB LED fixtures. Its wall-mount design with an intuitive handling and with a visual interface which makes very easy to use allows to install it everywhere when RGB control its is needed. No matter how expert is the user, HomeLed can be used by everyone without any programming knowledge

It has an encoder with push button that allows navigating between the 4 functions: Colour, Program, Speed & Brightness.

By pushing the encoder, the selected function will light a diferent colour. Then, turn the wheel to get the desired effect. Pushing it again to change the function to control.

The interface has been made to be intuitive. Four LEDs at the sides of the wheel show parameters and functions (Colour, Brightness, Speed and Program). LED light intensity changes to indicate their current value.

TECHNICAL DATA	HOME LED
Main Supply:	DC 12-24V 6A max.
DMX channels:	3 channels.
Factory preset programs:	10 programs.
Operating mode:	4 Functions: Colour, Brightness, Speed and Program.
Housing:	Polycarbonate.
Dimensions (WxHxD):	86 x 86 x 45 mm.
Weight:	100 g.



Connection example, using HomeLED and MiniDIM RGB to control LED LINE 10 strips.



Home·DIM

HOMEDIM

DMX wall-mount controller and dimmer

HomeDIM system is a great solution for architectural lighting control with mono channel fixtures. This 2.200W system is particularly useful for halls and galleries. It can be easily controlled from a unique place, whatever the size of the installation.

HomeDIM system is composed of two devices:

- **HomeDIM Power:** one channel dimmer (10A) controlled by HomeDIM Live through DMX protocol. It is configurable by DIP-Switches and features a DMX input with 2 additional pins used to supply HomeDIM Live.

- **HomeDIM Live:** wall-mount remote control that allows an intuitive control of light intensity in an installation. It works as a fader sending a DMX signal. Its beautiful design contributes to its integration in any place.

Thanks to DMX technology, **HomeDIM** can be used for many applications and in different ways. Thus, many **HomeDIM Power** can be connected to a same **HomeDIM Live**. The latter can also be used as a DMX controller for any other LED fixture. Another possibility is to integrate **HomeDIM Power** in a DMX network (without any **HomeDIM Live**).



HOME DIM LIVE



HOME DIM POWER



FEATURES

HOME DIM LIVE

- Wall-mount remote control.
- Emission of pure DMX signal (0-255) sent to a DMX channel.
- Configuration of DMX channel and fade time by DIP switch.
- External supply, using HomeDIM Power.

TECHNICAL DATA	HOME DIM LIVE
Main Supply:	DC 12 V.
Connection:	Terminals.
Housing:	Polycarbonate.
Control :	1 DMX channel.
Operating temperature:	-10° + 50°C.
Dimensions (WxHxD):	86 x 86 x 45 mm.
Weight:	200 g.



FEATURES

HOME DIM POWER

- Mono-channel dimmer (10A).
- Power unit for HomeDIM system.
- Controlled by HomeDIM Live (or any other DMX controller).
- Configuration of DMX channel by DIP switch.
- 2 additional pins for HomeDIM Live supply.
- Easily hidden behind false ceiling.

TECHNICAL DATA	HOME DIM POWER
Maximum load:	10 A.
Protocol:	DMX input and output.
Start channel :	Configurable by DIP switch.
Main supply:	AC 2530 V 50 Hz.
Dimensions (WxHxD):	185 x 125 x 47.5 mm.
Weight:	1.1 kg.



WD 2012 DMX

12 channel modular dimmer



Easily exchangeable power module.

This 12 channel modular dimmer features a 32 bit CPU software. Its large LCD display shows graphics and options.


Thanks to rear panel connectors, **WD 2012 DMX** receives DMX, MIDI and Analog signals. DMX address of each channel can be controlled, as well as response curve, output limit, preheat level and load check.

Parameters like execution speed and fade in/out time allows the configuration of its 12 internal memories. Master/Slave mode configuration increases the number of units connected to the dimmer. Access to all these functions and parameters is very easy, as it features an encoder with confirmation touches.

WD 2012 DMX is a safe device that features high voltage alarm, electronic fuse, load check and overheat detection system. It can be blocked to prevent any undesired handling. Its modular structure allows a fast and convenient substitution of channel power units, independently of each other and without having to disassemble the unit.

FEATURES

- 12 output channels.
- 10 A per channel (total: 120 A mono-phase or 40 A tri-phase).
- Inputs: DMX, MIDI, Analog (0-10 V).
- Dimensions (WxHxD): 483 x 178 x 436 mm.
- Weight: 31 kg.





WD 1512 DMX

12 channel modular dimmer

This 12 channel modular dimmer features a 32 bit CPU software. Its LCD display shows various options and values for personalization.

Thanks to rear panel connectors, **WD 1512 DMX** receives DMX, MIDI and Analog signals. Its DMX fail function allows the memorization of the last DMX signal that it receives. An analog mode is also available, as well as 12 internal memories to adjust with precision parameters like execution speed.

DMX address of each channel can be controlled, as well as response curve, output limit, preheat level and load check.

Parameters like execution speed and fade in/out time allows the configuration of the 12 internal memories. Master/Slave configuration increases the number of units connected to the dimmer. Access to all these functions and parameters is very easy, as it features an encoder with confirmation touches.

WD 1512 DMX has individual 10 A circuit breakers on each channel, in addition to fan forced cooling system. Its modular structure allows a fast and convenient substitution of channel power units, independently of each other and without having to disassemble the unit.

FEATURES

- 12 output channels.
- 10 A per channel (total: 120 A mono-phase or 40 A tri-phase).
- Inputs: DMX, Analog (0-10 V).
- Dimensions (WxHxD): 483 x 178 x 436 mm.
- Weight: 31 kg.

REAR PANEL





D 66 K3

12 channel modular digital dimmer



D 66 K3 is the most powerful digital dimmer from **WORK®**. It features in 3U rack units 12 channels with 25 A each. This is the perfect tool for fixed installations and touring, as it provides reliability, power and flexibility.

It features components for user security and a correct control of the dimmer. Double circuit breakers (1P+N) ensure electrical safety in case of short-circuits and electrical overload, cutting both phase and neutral conductors. Double fan forced cooling system provides uniform cooling, adequate with dimmer's power.

Dimensions of power components and inner design ensure robustness of the dimmer. Thus, internal electrical wiring has been reinforced to eliminate any drop in voltage, noise or unnecessary warming.

Thanks to its microprocessor-controlled electronic components, **D 66 K3** maintains a precise regulation, even in case of frequency variations, drop in voltage and noise in the network.

D 66 K3 is also an easy-to-use dimmer that provides a quick access to control menus, with its 16x2 character LCD display and keyboard.


FRONT PANEL INTERFACE.

The user interface features 3 main buttons for the menu that allows the configuration of the following parameters:

- Preheat level.
- Response time.
- Initial DMX channel.
- Response curve.
- Languages: Spanish, English, German and French.
- Creation and edition of 3 programs (up to 64 chases each) with time configuration between chases and pauses.
- Visualization of channel level (percentage) to check analog and DMX input.



Fixation lateral pieces and handles included.



Response curves available.

TECHNICAL DATA	D 66 K3
Main supply:	Mono-phase AC 230-240 V / Tri-phase (3P/N/E) AC 380 V.
Main supply frequency:	47 - 63 Hz.
Output power:	Mono-phase 18 kW / Tri-phase 55 kW.
Output current:	25 A per channel.
Load type:	Resistive and inductive (no more than 15% of nominal load if it is inductive).
Signal connector:	DMX in: XLR3 pin and male XLR5 pin. DMX thru: XLR3 pin and female XLR5 pin. Analog in: Sub-D (15 pin).
Main supply connector:	Terminals (L+N+E).
Output channel connector:	Terminals (L+N+E) x 12.
Dimensions (WxHxD):	483 x 132 x 412 mm. (3 19" HU rack).
Weight:	25 kg.

FEATURES

- 12 channel digital dimmer.
- DMX 512 and analog (DC 0-10 V) signal input, possibility to operate with both signal types simultaneously.
- Load capacity: 25 A per channel. Total 18 kW (mono-phase) and 55 kW (tri-phase).
- Individual DMX address and patchable response curve for each input channel (linear, quadratic, quadratic inverse, on/off).
- Preheat level on each channel.
- DMX buffer against connections fails.
- 2 pole circuit breaker (1P+N) for each channel.
- Auto-adjustment of power frequency between 47 and 63 Hz.
- Synchronization with microprocessor to detect and filter spurious frequencies produced in the power supply.
- Slow start with 4 second starting flange, avoiding current peaks.
- Program memory: 3 programs (64 programmable chases each).
- Lateral fixation accessories and handles.
- LED indicators for output levels of each channel, DMX signal detection and error detection.

REAR PANEL



PROTECTIONS

- Double magneto-thermal circuit breaker (1P+N) ensures electrical safety in case of short-circuits and electrical overload, cutting both phase and neutral conductors.
- Double fan forced cooling system (2 fans of 120 mm. diameter): automatic operating mode that reduces temperature to the prefixed value.
- Slow start with starting flange of 4 seconds avoids current peaks.
- Power frequency auto-adjustment between 47 and 63Hz (according to power input requirements) to do not affect the response curve. Associated with the Zero Crossing Detector (ZCD), it ensures stable output levels.
- Synchronization with microprocessor marks zero crossing points, detects and filters spurious frequencies produced in the power supply.
- Programmable protection: configuration of each output with a maximum level to avoid sudden level variations that can affect load (a 95% output level is efficient and almost undetectable).
- 0-100% duty cycle: internal filter and detection circuitry eliminate parasite noise and so allow using the full cycle during zero crossing process.



Analog signal input (DC 0-10 V).



DMX in/out interface (male/female XLR3-5).



Internal electronic components and mechanism.



D 40 K2

D 66 K2

12 channel dimmers

D 40 K2



D 66 K2



D 40 K2 and **D 66 K2** are two high performance dimmers of 12 channels (15 A each for **D 40 K2** and 25 A each for **D 66 K2**) that support DMX and analog signals.

Three programs are available (64 chases per program) to realize sequences and edit speed and channel intensity. Thanks to the advanced software for configuration, it is possible to patch each channel in an independent DMX address and edit parameters like pre-heat time, response curve, language, etc.

Because they support analog signal, these dimmers are compatible with controllers featuring a 0-10V output; they can even be controlled without any lighting controller, using menu and trigger buttons available on each channel.

As concerns electronic, they provide optimum results. Their power circuit has been reinforced and includes powerful TRIACS, ensuring the best performances in any situation.

REAR PANEL

D 40 K2

D 40 K2's rear panel has been designed to provide maximum versatility, featuring 12 schukos and 2 multi-connectors. It also includes connectors of 3 or 5 pins for DMX inputs and outputs, as well as a sub 15 connector for analog input.




D 66 K2

In only 3U rack units, **D 66 K2** reaches 60 kW power, 5 kW per channel with very low noise levels and an excellent temperature response.



Features (for both dimmers)

- 12 output channels.
- DMX 512 and analog (DC 0-10 V) signal input, possibility to operate with both signal types simultaneously.
- LED indicators for output levels of each channel.
- Temperature control by microprocessor.
- Programmable protection: configuration of each output with a maximum level to avoid sudden level variations that can affect load.
- 16x2 character LCD display.
- Supported response curves: linear, quadratic, quadratic inverse, on/off.
- Preheat level on each channel.
- Slow start of lamps (4 seconds) to switch on dimmer at full load.
- Mono-phase or Tri-phase mode (emergency operating mode in a unique phase).
- Power frequency auto-adjustment between 47 and 63 Hz.
- 0-100% duty cycle.
- 25 A TRIACs on **D 40 K2** / 41 A TRIACs on **D 66 K2**.
- Languages: Spanish, English, German and French.



Outputs divided in 2 groups of 6 channels, each one featuring 6 schukos and a 16pin multi-connector.


TECHNICAL DATA	D 40 K2	D 66 K2
Tri-phase power output:	27.5 kW.	55 kW.
Mono-phase power output:	18 kW.	18 kW.
Output channels:	12.	12.
Output current:	15 A /channel.	25 A /channel.
DMX input:	XLR3 and XLR5.	XLR3 and XLR5.
Dimensions (WxHxD):	442 x 177 x 412 mm.	442 x 132 x 412 mm.
Weight:	18 kg.	25 kg.



DMX and analog signal outputs.

Four configurable response curves are available:

1. Linear: (Blue)
2. Quadratic: (Green)
3. Quadratic Inverse: (Yellow)
4. ON/OFF: Change from on to off at 50% with a flange between 45% and 55% (Red).





WD 90K DMX

6 channel dimmer




This dimmer, electronically controlled by processor, features 6 channels of 15 A each and many configuration functions and adjustments.

DMX address of each channel can be controlled, as well as response curve (linear, switch and square), output limit, preheat level and fade time. All these parameters are visualized on the LCD display.

WD 90K DMX also features 24 programmable scenes, 10 shows (from the previous 24 scenes) and 90 factory-programmed chase programs. Scenes can be easily patched on DMX channels, selecting the assigned function, that means, with one DMX channel can trigger an scene of 6 dimmer channels. Master/Slave configuration increases the number of units connected to the dimmer.

Individual circuit breakers for each channel protect the device, as well as a security system that reduces output by 50% when temperature exceeds a certain value. A routine check verifies minimum and maximum values for each channel. Using the menu, it is possible to get access to any information regarding the unit (working hours, temperature o DMX levels). It can be blocked to prevent any undesired handling.



Individual circuit breakers.



LCD display for parameter visualization.

FEATURES

- 6 channel DMX dimmer.
- Load capacity: 15A per channel.
- Mono-phase or Tri-phase mode.
- 24 programmable scenes.
- 90 factory preset programs.
- Independent configuration of channel parameters.
- 10 shows.
- Patchable channels.
- Master/Slave mode.
- Memory against power supply failure.
- Dimensions (WxHxD): 483 x 88 x 390 mm.
- Weight: 9 kg.

WD 620 DMX

6 channel dimmer



This dimmer, electronically controlled by processor, features 6 channels of 20 A each and many configuration functions and adjustments easily accessible thanks to its intuitive menu.

DMX address of each channel can be controlled, as well as response curve (Linear, S-curve, Square and No-Dim), output limit, preheat level and fade time. All these parameters are visualized on the LCD display. A control function is also available using external analog signal (DC 0-10 V).

12 programmable chases with adjustable speed allow the execution of programs whose channel values are directly configured on dimmer. If DMX connection fails, a routine allows using 3 other modes: Hold (using last DMX signal stored), analog or using existing chase programs.

Individual circuit breakers for each channel protect the device, as well as a security system that protects it against overheating and short circuits.



FEATURES

- 6 channel DMX dimmer.
- 20 A per channel.
- Mono-phase or Tri-phase mode.
- DC 0-10 V input for analog mode.
- Patchable DMX channel address.
- Configurable input and output limits.
- 12 programmable chases with adjustable speed.
- 3 operating modes available in case of DMX connection failure.
- Memory against power supply failure.
- 20 A magneto-thermal circuit breaker for each channel.
- Dimensions (WxHxD): 483 x 88 x 390 mm.
- Weight: 9 kg.



LCD display and key functions.



WD 616 KMT

6 channel dimmer



REAR PANEL



With 6 channels of 16 A each, this versatile and functional dimmer ensures lighting intensity control and represents a great answer for most of the users. It is compatible with DMX 512 signals and has a tri-phase supply.

It has DIP switches to patch DMX start channel address. Each channel can be controlled independently from the others; LED indicates dimmer value.

FEATURES

- 6 channel DMX dimmer.
- Input signal: 512 DMX.
- Load capacity: 16A per channel. Total 22 kW (Mono-phase) or 7.4 kW (Tri-phase mode).
- DMX start channel address patchable by DIP switch.
- Individual slide dimmer control switches.
- 20A circuit breaker for each channel.
- LED indicators for each channel output level and for DMX signal presence.

TECHNICAL DATA	WD 616 KMT
Main supply:	Mono-phase AC 230/240 V. Tri-phase (3P/N/E) AC 380 V.
Output power:	Mono-phase 7.4 kW / Tri-phase 22 kW.
Output current:	16 A per channel.
Load type:	Resistive and inductive (no more than 15% of nominal load if it is inductive).
Signal connector:	DMX in: XLR3 pin and male XLR5 pin. DMX thru: XLR3 pin and female XLR5 pin.
Main supply connector:	Terminals (L+N+E).
Output channel connector:	Terminals (L+N+E) x 6.
Dimensions (WxHxD):	483 x 88 x 381 mm. (2 HU rack 19").
Weight:	8.38 kg.



ARCDIM 610 DMX

6 channel dimmer

ARCDIM 610 DMX has been designed for architectural lighting and fixed installations. It features a 6 scene programmer and allows time fade control between scenes. The latter can be stored into the dimmer and monitored thanks to LED indicator that also informs about intensity (in dimmer mode).

ARCDIM 610 DMX includes a DMX start channel address that can be configured (visualization on display). Output current supported by each channel can reach 10 A (each one with its own circuit breaker). A fan forced cooling system protects it from overheating.

The dimmer also features a wall-mount system and provides a remote control that allows hiding the dimmer and not harming installation design.

FEATURES

- 6 channel DMX dimmer for architectural lighting and fixed installations.
- Load capacity: 10 A per channel (total 60 A).
- Individual slide dimmer control switches.
- 4 segment LCD display.
- Control and storage of scene fade time.
- Possibility to fill out/in the dimmer section unit.
- Minimum and maximum levels configurable on each output.
- DMX Input/Output connection.
- Magneto-thermal circuit breaker for each channel.
- Fan forced cooling system.
- Wall-mount system.
- Main supply: AC 230 V 50 Hz.
- Dimensions (WxHxD): 270 x 480 x 120 mm.
- Weight: 10.3 kg.



Fixation holes.



External controller (included).



Menu interface.



UNIDIM 1

DUODIM

1/2 channel dimmers

UNIDIM 1



DUODIM



UNIDIM 1 and **DUODIM** are ultra compact DMX dimmers with one or two channels (depending on model) and a maximum load of 10 A per channel. They can be used as a chaser to remotely switch lighting effects like scanner or moving head that do not have any assigned DMX channel. Thanks to their compact size, they can be easily placed on DIN rails or trusses.

The software provides an intuitive menu for parameters edition like maximum dimmer levels or DMX address channel. User can change from dimmer operating mode to chaser one (called Switch mode). The latter allows intensity manual adjustments for each channel. For maximum convenience, all the functions are shown on the display.

These dimmers are also compatible with switch devices like foot pedals, but also with connection panels when they are used as a driver. They respectively include one and two schuko connectors with protection lid for power output.



Local DIM control (UNIDIM).



Local DIM control (DUODIM).

FEATURES

- 1 channel (**UNIDIM 1**) or 2 channel (**DUODIM**) DMX dimmers/chasers.
- 10 A channel load/channel.
- Two operating modes: Dimmer or Switch.
- DMX addressing, DIM Preset and DIM Limit.
- Manual dimmer (HTP) to indicate threshold start.
- Remotely controllable (optional).
- Memory against power supply failure.
- Link connection to other units.
- Internal rail for clamp fastening.



Internal rail for clamp fastening.



Control panel.

TECHNICAL DATA	UNIDIM 1	DUODIM
Main supply:	AC 230 V, 50 Hz.	AC 230 V, 50 Hz.
Max. total current:	10 A.	10 A. per channel.
Number of channels:	1.	2.
Output connection:	1 schuko connector with protection lid.	2 schuko connectors with protection lid.
DMX output:	XLR3 pin.	XLR3 pin.
DMX input:	XLR3 pin.	XLR3 pin.
Dimensions (WxHxD):	200 x 82 x 67 mm.	300 x 82 x 67 mm.
Weight:	1.1 kg.	2.72 kg.



STAGE 12 P DMX

Controller and 12 channel DMX dimmer

This unique device combines a controller and a 12 channel DMX dimmer: it results particularly convenient for users that will take advantage of its portability, capacity to create and edit control programs and its own dimmer for direct connection to lighting systems.

Regarding lighting control, it has the same features as **STAGE 1624 DMX** (see pg.16) but with 12 channels, supplying up to 8 factory preset programs and 16 others for user configurations. Each channel has a flash button to switch it on/off and for manual mode. A keyboard and a remote control unit can also be connected to the device to realize switching functions. Programs allow speed synchronization with internal speed, Tap Sync function, audio synchronization system (thanks to the internal microphone) or even with MIDI function.

Regarding power section, 5 A output current per channel (with schuko connectors featuring protection lid and individual fuse) ensures the perfect operation of connected fixtures. A DMX output is also available for additional dimmers.

FEATURES

- 12 DMX control channels for conventional lighting.
- 24 programs: 16 (user) + 8 (preset).
- Flash button for each channel.
- Memory against power supply failure.
- Speed, audio, MIDI and Tap Sync synchronization.
- Connection for external foot switch and fog machine trigger.
- DMX polarity selector.
- Password to avoid any undesired external manipulations.
- Connection for remote control (switch Off/On).
- Output channel: 5 A.
- Main supply: 2 phases, AC 230 V 16 A /phase max.
(Phase A: channels 1 to 6 / Phase B: channels 7 to 12).
- Dimensions (WxHxD): 483 x 266 x 182 mm.
- Weight: 8.6 kg.

REAR PANEL





STAGE 6P ANALOG

Controller and 6 channel DMX dimmer



REAR PANEL



This 6 channel mixer offers all the features of an analog dimmer. Each channel supports up to 5 A load, with schuko connectors at the rear panel of the device. Individual protection fuse ensures that if one output channel fails, the others will not be affected. Three operating modes are available: Auto-chase (adjustable speed), Audio-chase (audio synchronization) and manual dimmer.

FEATURES

- 6 channel mixer with built-in dimmer.
- Output channels: 5A max. per channel.
- Chaser by audio or internal speed synchronization.
- Flash and Blackout functions.
- Main supply: AC 220-240 V 50 Hz.
- Dimensions (WxHxD): 350 x 110 x 175 mm.
- Weight: 3.3 kg.

STAGE 4 P ANALOG

Controller and 4 channel DMX dimmer



REAR PANEL



STAGE 4P ANALOG is a 4 channel mixer with built-in dimmer, designed in a 19" rack format, with an easy access to connectors. Each channel supports up to 5 A load, with schuko connectors at the rear panel of the device. Individual channel levels and Master level can be adjusted, and LED indicators show the active state of each channel.

The unit provides a switch for chaser's operating mode selection, so user can choose between internal speed and audio signal synchronization. Both modes feature speed and level controls.

Whereas Flash function allows the individual switching on/off of channels, general and blackout functions are useful to switch all channels on/off at the same time.

FEATURES

- 4 channel mixer with built-in dimmer.
- Output channels: 5 A max. per channel.
- Chaser by audio or internal speed synchronization.
- Flash and Blackout functions.
- Main supply: AC 220-240 V 50 Hz.
- Dimensions (WxHxD): 483 x 88 x 234 mm.
- Weight: 4.5 kg.



PROLIGHT 6 ANALOG

Controller and 6 channel DMX dimmer

REAR PANEL



PROLIGHT 6 ANALOG is a 6 channel mixer with built-in dimmer, designed in a 19" rack format, with an easy access to connectors. Each channel supports up to 5 A load, with schuko connectors at the rear panel of the device. Individual channel levels and Master level can be adjusted. 10 preset programs are available and they can be visualized in the display.

Regarding chaser operating modes, user can choose between internal speed and audio signal synchronization. Both modes feature speed and level controls.

FEATURES

- 6 channel mixer with built-in dimmer.
- Output channels: 5 A max. per channel.
- Chaser by audio or internal speed synchronization.
- Flash and Blackout functions.
- Main supply: AC 220-240 V 50 Hz.
- Dimensions (WxHxD): 483 x 88 x 234 mm.
- Weight : 5 kg.



LPX 12 DMX

12 DMX/Analog channel chaser

REAR PANEL



This is a 12 DMX/Analog channel driver and chaser, particularly useful to activate spots, switch on and switch off lighting effects. Start channel address can be configured by user, and analog signals have priority on DMX ones.

FEATURES

- 12 DMX/analog channel driver and chaser.
- Analog signals have priority on DMX ones.
- Channel autocheck function
- Output channels: 5A per channel.
- Memory against power supply failure.
- Main supply: AC 220-240 V 50 Hz.
- Dimensions (WxHxD): 483 x 90 x 240 mm.
- Weight: 4.92 kg.



WDP 4 DMX

4 channel DMX chaser and dimmer

WDP series are chasers and dimmers that provide an efficient solution for mobile installations.

This series is composed of 3 models with 5 A per channel (4 output channels via IEC for **WDP 8 DMX**, schukos for the other models).

WDP 4 DMX ANALOG is a simple chaser, whereas **WDP 4 DMX** and **WDP 8 DMX** also provide DMX digital control and dimmer.

The three devices have factory preset memory chases with adjustable speed and audio synchronization. To control DMX addressing and output level, **WDP 4 DMX** and **WDP 8 DMX** include a menu accessible using display and four touch buttons.



Key touches for Mode and Menu selection. LCD display for visualization.

MODE	MENU	DISPLAY
RECEIVE	DMX CHANNEL	R:001 — R:512
	TOTAL DMX CHANNEL	CH:01 / CH:02 / CH:04
	DIMMER / SWITCH	C1 — C4 / d - 5
CHASE	CHASE PROGRAM	P:01 — P:16
	CHASE SPEED	SP:01 — SP:99
	CHASE DIMMER	d:000 — d:100
	DIMMER / SWITCH	C1 — C4 / d - 5

Operating modes (chasers, DMX values, dimmer) shown on display.



DMX input and output interface.

FEATURES

- 4 channel DMX chaser and dimmer with up to 5 A per channel (max.16 A load)
- Compact size for easy transport.
- Operating modes: Adjustable speed chaser and DMX dimmer.
- Memory against power supply failure.
- Main supply: AC 230 V 50 Hz.
- Dimensions (WxHxD): 188 x 212 x 75 mm.
- Weight: 2.4 kg.

WDP 8 DMX

4 channel DMX chaser and dimmer



FEATURES

- 4 channel DMX chaser and dimmer with up to 5 A per channel (max.16 A load).
- Compact size for easy transport.
- Operating modes: Adjustable speed chaser (16 programs) and DMX dimmer.
- Double output per channel with IEC connectors.
- Memory against power supply failure.
- Main supply: AC 230 V 50 Hz.
- Dimensions (WxHxD): 190 x 255 x 75 mm.
- Weight: 2.4 kg.

WDP 4 ANALOG

4 channel chaser



Remote control (included).

FEATURES

- 4 channel chaser with up to 5 A per channel (max.16 A load).
- Compact size for easy transport.
- Operating modes: Adjustable speed chaser and audio synchronization.
- Internal microphone.
- Stand By and Full on functions.
- Remote control for all functions.
- Possibility to connect other units.
- Memory against power supply failure.
- Main supply: AC 230 V 50 Hz.
- Dimensions (WxHxD): 210 x 260 x 75 mm.
- Weight: 2.2 kg.





DMX PLAYER 5

DMX PLAYER/RECORDER

DMX PLAYER 5 is an advanced DMX player/recorder featuring 256 channels. Its control panel has direct access on internal memory to find and trigger chases, scenes or shows.

With its internal memory (24 banks of 40 scenes /total 960), 40 chases with up to 99 steps each and 8 shows with up to 99 scenes, it is very convenient when users only have to trigger shows or/and when they do not have any knowledge regarding programming. Thus, a lighting programmer can prepare a large number of scenes and final user will just have to click to trigger them.



RACK SCAN
(optional)



FEATURES

- 256 DMX channels + 40 additional switch channels (On/Off).
- 24 banks of 40 programmable scenes (total 960 scenes).
- Each scene consists in 256 DMX channels with activated fade time.
- 40 chases, each one with 99 steps.
- 8 shows, each one with 99 scenes (speed and fade time for independent scene).
- Data exchange capacity between two units.
- Master blackout function.
- Internal microphone for audio synchronization.
- Units can be linked in Master/slave mode.
- DMX polarity selector.
- Memory against power supply failure.
- Main supply: DC 9 V, 500 mA min (included power supply unit)
- Dimensions (WxHxD): 483 x 132 x 73 mm.
- Weight : 2.2 kg.



DMX RECORDER 19''

Real time DMX recorder

REAR PANEL



This real time DMX recorder has been designed for lighting professionals, as it allows recording any triggered scenes (for both signal levels and chases between scenes) from consoles connected to it. The 19" rack format version is appropriate for fixed installations, as it can be integrated with other control elements.

Internal memory provides 6 shows (4 + Start program + End program) and other 33 using the 32MB compact flash card (special slot for CF cards).

Six operating modes are available: Manual, Autostart, DMX Mon, DMX Trigger, Program and Set up. Another function (SMPTE trigger) allows speed synchronization with 24/25/30 frames.


Terminal block gets access to Play/Stop/Pause functions as well as 4 of the scenes. All the information is visualized on LCD display.

FEATURES

- Real time DMX recorder (512 channels).
- 4 internal scenes.
- 33 additional scenes using CF cards.
- Slot for 32MB CF cards.
- External control of Play/Stop/Pause functions.
- SMPTE trigger control of 24/25/30 frames.
- Main supply: DC 9 V, 500 mA min (included power supply unit).
- Dimensions (WxHxD): 483 x 44 x 80 mm.
- Weight: 1.5 kg.



DMX interface and SMPTE triggering.



Terminal block for the external control of 4 internal scenes.



Slot for 32MB CF card.

DMX RECORDER

Real time DMX recorder

Available connections for both models.



DMX interface and SMPTE triggering.



Terminal block for the external control of 4 internal scenes.



Slot for 32MB CF card.



This real time DMX recorder has been designed for lighting professionals, as it allows recording any triggered scenes (for both signal levels and chases between scenes) from consoles connected to it. This portable version is more appropriate for mobile and touring applications.

Internal memory provides 6 scenes (4 + Start program + End program) and other 33 using the 32MB compact flash card (special slot for CF cards). Six operating modes are available: Manual, Autostart, DMX Mon, DMX Trigger, Program and Set up. Another function (SMPTE trigger) allows speed synchronization with 24/25/30 frames.

Terminal block gets access to Play/Stop/Pause functions as well as 4 of the scenes. All the information is visualized on LCD display.

FEATURES

- Real time DMX recorder.
- 4 internal scenes.
- 33 additional scenes using CF cards.
- Slot for 32MB CF cards.
- External control of Play/Stop/Pause functions.
- SMPTE trigger control of 24/25/30 frames.
- Main supply: DC 9 V, 500 mA min (included power supply unit).
- Dimensions (WxHxD): 220 x 130 x 55 mm.
- Weight: 1.2 kg.



LM-3 series

NEW



LM-3E



LM-3R

LM-3 series is probably the easiest way to transport DMX through an Ethernet network, as it directly integrates itself in an existing network. This is particularly useful for older installations that cannot be physically modified: LM-3 series provides DMX signal anywhere in the building.


In order to get it, the system is composed of emitters (LM-3E) that put DMX frames in the Ethernet network, and receivers (LM-3R) that extract DMX signals from the Ethernet network. To send and receive DMX, both LM-3E and LM-3R use the same protocols: WorkNet Control (proprietary protocol) and ArtNet.

Plug-and-play: Installation is easier than ever!

One of the main advantages of this system is that it is very easy to install. User does not have to configure network, but only to connect to network one LM-3E and one or many LM-3R. They detect each other in the Ethernet network and start to emit/receive DMX signals: you don't need any network knowledge to start using it.



Integrated WEB SERVER for LM-3E and LM-3R configuration. It is possible to edit IP address and unit description.



Control of DMX fixtures (SIDIUS 1200) from a DMX console (SCAN 1000 DMX) through an Ethernet network. LM-3E and LM-3R allow sending DMX information through an existing network. Both units use WorkNet proprietary protocol.



LM-3E and LM-3R front panels with LAN connection, group selector and LED for DMX and Ethernet signal.



LM-3R rear panel with DIP switch block for protocol selection (WorkNet or standard ArtNet and Subnet mask).

Multi-universe and multi-system.

If LM-3E (emitter) has been designed to send one DMX universe (512 channels), additional universes can be sent together: a group selector puts many units together, each one supporting a DMX universe. In the same manner, each LM-3R will be suitable for one DMX universe.

It is also possible to use many LM-3E to send DMX signals coming from different DMX controllers: in other words, many DMX networks can be dumped in a same Ethernet network.

Total network integration.

WorkNet Control protocol provides a total compatibility with any networks used by today's computers. This is particularly interesting for LM-3 users because they can integrate fixtures in networks that already have computers. In addition, this is a Unicast protocol: it ensures that LM-3 series uses minimum bandwidth.

Lightmouse
series



NEW

LM-3E

DMX to Ethernet interface

LM-3E is a DMX to Ethernet converter that sends DMX signals in an existing Ethernet network.

It has been preset to be automatically integrated in Ethernet networks, so no configuration is required. Nevertheless, it is fully configurable and user can, if he wants to, change the system IP address.

Thanks to its group selector, many **LM-3E** units can be sent in a same network, transporting thus various DMX universes together. This is a great solution for consoles that use more than one DMX universe or for many independent DMX controllers.

Dimensions (WxHxD): 80 x 45 x 80 mm.



NEW

LM-3R

Ethernet to DMX interface / ArtNet node

LM-3R for its own is an Ethernet to DMX converter. There are two ways to use it.

Plug-and-play Ethernet to DMX converter.

Its main function is to receive frames sent by **LM-3E**, avoiding any DMX configurations: it comes ready to use.

ArtNet node.


Using the DIP switch, user can change the value of **LM-3R** and turns it into an ArtNet node of one DMX universe. Thus, **LM-3R** becomes compatible with any standard ArtNet system, receiving DMX frames from lighting consoles using this standard protocol.

Total network integration using ArtNet2 protocol.

ArtNet2 is a Unicast protocol so it makes integration in Ethernet networks easier, using minimum bandwidth.


Dimensions (WxHxD): 80 x 45 x 80 mm.

ArtNet
COMPATIBLE



LM-3 series using a DMX multi-universe controller.

System control for 2 groups of different DMX fixtures (SIDIUS 1200 and SIDIUS 575 SPOT) from a DMX console through Ethernet network. **LM-3E** and **LM-3R** allow sending DMX information (each universe is separated from the other) after emission/reception group configuration. Both units use **WorkNet** protocol.



LM-3 series using a DMX controller with ArtNet protocol.

System control for 2 groups of different DMX fixtures (SIDIUS 1200 and SIDIUS 575 SPOT) from a DMX console (LightON 3) through Ethernet network. The console allows a direct ArtNet connection. **LM-3R** converts signal or DMX protocol to control units.



DMX-NET series

DMX/ArtNet node with video interface



DMX-NET 8

NEW



DMX-NET 48

With the **DMX-NET series**, **WORK®** provides a unique range of "all-in-one" products for video lighting professionals.

ArtNet node.

DMX-NET works as an ArtNet node, fully configurable and featuring 8 or 48 universes (depending on the model).

Thanks to ArtNet technology, up to 255 universes can be sent through an Ethernet network, taking advantage of the fast data transfer (faster than a DMX network). This is particularly useful to control LED animation devices that require many channels, or to send DMX information of a large event through a unique Ethernet cable.

An advanced video system for DMX LEDs.


DMX 1000 K proprietary protocol allows the edition of **DMX-NET** in an operating mode reaching up to 1 Mbit/s for each output of DMX universe. Most of our LED fixtures, like **PUZZLED**, **VIDEO TUBE**, etc. are suitable for this speed. This is very convenient for users because a DMX line can support up to 4 universes. An intuitive software (included) allows an efficient control on the overall lighting system.

Video and DMX recorder/player.

Thanks to their internal memory, **DMX-NET** devices can store important DMX frames (like the one resulting from video triggering) to be interpreted by a DMX system (LED fixtures in most cases). It converts video into DMX signal that can be directly triggered, or stored in **DMX-NET** memory. An internal clock allows programming show triggering. The latter can also be triggered using 3 DMX channels (thanks to the DMX TRIGGER function).

Integration with ArKaos.

A special license of ArKaos VJ for **DMX-NET** allows using 1 Mbit/s speed for DMX outputs, ensuring an easy control of the device.



DMX-NET 8 working as an ArtNet node. **LightON 3** console sends control information using ArtNet protocol and it is interpreted by **DMX-NET 8** (512 channels for each universe, total 4096 channels). 5 universes for a LED screen, 1 for moving heads and 2 others for dimmer control.



Ethernet port and subnet mask assignment in ArtNet.

FEATURES

- Standard ArtNet node with 8 or 48 output DMX universes in standard DMX mode.
- Protocols: ArtNet, DMX 512 and CL 100 M proprietary protocol.
- Internal memory for 32 DMX show storage.
- Included software that converts video into DMX frames (at 1 Mbit/s).
- Suitable with ArKaos.

NEW

LM-2

Bidirectional DMX/USB interface



A very small but powerful device for lighting control.

New **LM-2** is the evolution of first LightMouse device. This bidirectional DMX/USB interface (input/output DMX interface) is a small and lightweight box that allows:

- Working as a 'USB to DMX interface' to control from a unique computer, a full 512 channel lighting system.
- Working as a 'DMX to USB interface': with an application like **ARKAOS VJ DMX** the DMX signal can control the computer and interact with the software.

Thanks to **LM-2**, lighting designers can take advantage of a small and strong device, being particularly appropriate for mobile uses where there is always a place for it.

A versatile device.

There are many ways to use **LM-2**, so users can realize different configurations with this unique device. The following connection schemes (below) show how **LM-2** can be used as a DMX output or a DMX input (with a Media server).


FEATURES

- Controls up to 512 channels.
- 1500 V full isolation (data & power lines to protect your computer from surges).
- USB port compatible with USB 1.1 or 2.0.
- USB cable and CD drivers for Windows, OSX and Linux.
- Compatible with most controllers and media servers of the market.
- Main supply: 300 mA. (via USB).
- Dimensions (WxHxD): 80 x 45 x 54 mm.
- Weight: 300 g.



LM-2 used to control a Media Server.

LM-2 can be used as a USB output to connect a DMX console to a PC (running Arkaos or other video software).



LM-2 used as a DMX output.

Connected to a PC via USB, it is used as a DMX output for moving head and dimmer connection (controlled by software or by their own controller).



IS 2

2 way splitter

NEW




IS 2 is a 2 way splitter with total isolation between input and output. It is useful in installations that need to double DMX signal to control two different lighting device frames.

Its small size is another advantage, because it can be supplied by both terminal blocks and external supply. It includes input and output XLR3 pin, as well as fixation points to be mounted on walls and ceilings.

Dimensions (WxHxD): 80 x 45 x 80 mm.

Weight: 380 g.



Connection example with IS 2 splitter that receives DMX signal frame and sends it to its 2 outputs (2 lines of moving heads).

IS 6

6 way splitter


NEW



IS 6 is a 6 way splitter with total isolation between input and output. It is very intuitive and particularly useful in installations that need to send DMX signal to different lighting device frames (moving heads, scanners, dimmers, LED fixtures, etc.). Its small size is another advantage, because it can be supplied by both terminal blocks and external supply. It includes input and output XLR3 pin, as well as fixation points to be mounted on walls and ceilings.

Dimensions (WxHxD): 80 x 45 x 113 mm.

Weight: 470 g.



Connection example with IS 6 splitter that receives DMX signal frame and sends it to its 6 outputs: three for moving head control, one for dimmer control, two for RGB LED fixtures control (through MINIDIM RGB driver).



DMX PATCHER



Device for DMX addressing and signal buffer



DMX PATCHER is a device that patch the input DMX signal frame, in a starting address adequate to an installation previously created.

This functions is very common in installations where have been added several DMX devices and it is very difficult to setup them again, so putting a **DMX PATCHER** at the beginning of the control line, it allows to assign this line to a chosen channel.

Another function of this unit is like DMX signal booster, helping to get an optimal control signal during extenses lines.



TECHNICAL DATA	DMX PATCHER
Input connection:	Terminal block (3p).
Output connection:	Terminal block (3 p).
Main supply:	DC 12/24 V, 100 mA.
Dimensions (WxHxD):	88.2 x 45.7 x 16.6 mm.
Weight:	250 g.

DMX PATCHER configuration example. It is connected to a line which start address is 1 and must be assign the channel 10 of DMX frame. Marking the channel 10 in the IN ADDR dip-switch block, it will be converted internally, in the channel 1 on DMX PATCHER output.

Example: One concrete channel assignment from the DMX frame to a different channel like starting address in a control line. In this case, channel 10 in the DMX frame will control a devices line which start in address is configured in the channel 6. The DMX frame channel will marked in the IN ADDR block (10) and the channel 6 in the OUT ADDR block.





WD 4 SPLITTER & BUFFER

4 way DMX signal splitter



LATERAL PANEL



This 4 way DMX splitter (1 input / 4 outputs) ensures total isolation between input and output (and between outputs). The latter have a double DMX connection with XLR3 and XLR5 connectors. Each output features an independent driver to extend DMX conduction and +/- DMX signal indicators.

Thanks to its Link out/Terminate selector, it is possible to connect other fixtures and indicate the end of connection chains and so prevent the DMX output from errors.

FEATURES

- 4 way signal splitter.
- Total isolation between connections.
- Double DMX connection (XLR3 – XLR5).
- Link out/Terminate selector.
- Dimensions (WxHxD): 483 x 88 x 120 mm.
- Weight: 2.3 kg.

WD 6 SPLITTER & BUFFER

6 way DMX signal splitter



REAR PANEL



WD 6 SPLITTER & BUFFER differentiates itself from previous model as it features 6 ways (1 input and 6 outputs) and sizes only 1U rack unit.

Others features are all the same: total isolation between input and output (and between outputs), double DMX connection with XLR3 and XLR5 connectors, independent driver to extend DMX conduction and +/- DMX signal indicators.

Thanks to its Link out/Terminate selector, it is possible to connect other fixtures, indicate the end of connection chains and so prevent the DMX output from errors.

FEATURES

- 6 way signal splitter.
- Total isolation between connections.
- Double DMX connection (XLR3 – XLR5).
- Link out/Terminate selector.
- Dimensions (WxHxD): 483 x 44 x 135 mm.
- Weight: 2.2 kg.



C 72 DMX

DMX/Analog converter

REAR PANEL



C 72 DMX is a DMX to Analog signal converter suitable for 72 analog channels.

It converts DMX and MIDI signals into analog signals. It allows using an analog dimmer with DMX consoles, setting parameters like DMX start address channel, MIDI note selection, etc.

It also works as a chaser with adjustable speed to record and program scenes from a DMX console. With its Hold function, it provides memory against current failures that maintain the last DMX configuration.

C 72 DMX sends analog signals through SUB-25 connectors. Their input voltage can be set (from DC +10V, DC +15V or DC +20V) with DIP switches. Polarity can be switched too.

FEATURES

- DMX to analog signal converter.
- Adjustable voltage level for outputs (DC 10, 15, 20 V).
- Voltage polarity selector.
- 72 channel chaser operating mode.
- Programmable DMX start address channel.
- Programmable chase speed.
- Memory against current failures.
- Main supply: 230 V AC 50 Hz.
- Dimensions (WxHxD): 483 x 44 x 120 mm.
- Weight: 2.3 kg.



FS 4 DMX

DMX flash controller

REAR PANEL



This device controls 4 DMX flashes with up to 4 channels and/or 4 analog flashes.

It features 20 programs (19+1 audio) that are controllable using one of the different operating modes: Audio, Program, Speed and Dimmer. Parameters like speed, audio intensity and dimmer level are available, in addition to a selector for trigger, Stand By and Full On functions.

Line output connection reaches up to 100 mV for audio mode, and an input polarity selector is available for DMX operating mode.

FEATURES

- DMX flash controller with up to 4 channels and/or 4 analog flashes.
- 20 chase programs.
- Audio mode for recorded scenes.
- 4 analog outputs for trigger pulses.
- Configuration of speed, audio intensity and dimmer.
- Stand By and full on functions.
- Memory against current failures.
- Main supply: DC 9 V, 500 mA (included).
- Dimensions (WxHxD): 483 x 44 x 76 mm.
- Weight: 1.2 kg.



MERGER DMX

DMX signal merger and backup system



REAR PANEL




MERGER DMX mixes two DMX signals coming from two different input sources (A+B) into one DMX output. DIP switches of **MERGER DMX** set up the merging mode, resulting in a unique output signal (from A+B inputs). It automatically changes DMX channel addresses to optimize available channels of the console (see scheme below). It also allows using a console as backup of another one.

The device provides three operating modes, each one with its own features:

- HTP mode: when there are two input signals, the priority goes to the highest one.
- Backup mode: Signal at A input goes to output, and if it disappears, it is substituted for B input signal.
- Merge mode: the device allows mixing the two input signals in a unique output signal (see scheme below).

FEATURES

- DMX signal merger for lighting control.
- 3 operating modes: HTP, Backup and Merge modes.
- Operating modes and start channel address seleccionable by DIP switches.
- DMX inputs and outputs: Male XLR3 (In) and Female XLR3 (Out) on front and rear panels.
- Main supply: DC 9 V, 500 mA (included).
- Dimensions (WxHxD): 483 x 44 x 73 mm.
- Weight: 1.15 kg.





Voltage regulators




Over the last years, voltage regulators have become one of the essential devices of touring applications.

Taking into account that almost all of the events use computers, lighting controllers, etc., voltage regulators represent the most secure device to protect material against voltage variations. This is even more important when supply comes from mobile supply units (generators) as provided current is mostly unstable.

From **EST 1 K** to the powerful **ESD 10 K**, **WORK®** presents an exhaustive series of voltage regulators as an answer to user needs for their different applications, ensuring in any case material safety.

When main power supply comes to variable transformer, control system measures output voltage and current. If it exceeds a predetermined threshold, protection relay will activate itself to keep safe electrical devices.

Thanks to voltage sample, it is possible to control voltage transformation relation, maintaining thus voltage output equal in the determined value. LCD display shows any information regarding current voltage at inputs and outputs.



These three units maintain output supply at a predetermined value, with an input voltage that constantly oscillates between 140 and 250 V AC. This allows the connection of loads equals to 500W (EST 500), 1000W (EST 1K) or 2000W (EST 2K).

They feature different protections to ensure output signal integrity: protections against overload, overvoltage or output short-circuit. An additional rearmable fuse is available on rear panel.

To avoid noises coming from the interrupter, these devices feature a time delay circuit (configurable between 3 and 6 sec.). After this time, normal operating mode starts automatically.

A large display shows the information regarding devices status, like input, output and current voltage.

EST 500

EST 1 K

EST 2 K

Voltage regulators



EST 500



EST 1 K



EST 2 K

TECHNICAL DATA	EST 500
Load capacity:	500 VA.
Main supply:	AC 140-250 V.
Output:	AC 220 V \pm 3%.
Frequency:	50 Hz / 60 Hz.
Time delay:	3 to 6 sec.
Dimensions (WxHxD):	150 x 242 x 180 mm.
Weight:	5.8 kg.

TECHNICAL DATA	EST 1 K
Load capacity:	1000 VA.
Main Supply:	AC 140-250 V.
Output:	AC 220 V \pm 3%.
Frequency:	50 Hz / 60 Hz.
Time delay:	3 to 6 sec.
Dimensions (WxHxD):	150 x 242 x 180 mm.
Weight:	6.6 kg.

TECHNICAL DATA	EST 2 K
Load capacity:	2000 VA.
Main supply:	AC 140-250 V.
Output:	AC 220 V \pm 3%.
Frequency:	50 Hz / 60 Hz.
Time delay:	3 to 6 sec.
Dimensions (WxHxD):	150 x 242 x 180 mm.
Weight:	8.1 kg.

REAR PANEL



FEATURES


- Microprocessor (MPU) for control and regulation.
- Large LCD display for data.
- Highly precise regulation.
- Protections against overload, overvoltage or output short-circuit.
- Time delay circuit configurable between 3 and 6 sec.



ESD 5 K/2

EST 519/2

Voltage regulators



ESD 5 K/2




EST 519/2

These two voltage regulators maintain a constant output supply when voltage oscillates between 140 and 250 V. It is possible to connect a 22 A fix load. As many fixtures performance depends on voltage, it is essential to ensure the regulation and control on these values.

Features and operating modes are the same for both models but each one has its own format: ESD 5 K/2 provides handles for an easy transport whereas EST 519/2 has been designed in a 19" rack format for its integration in fixed installations. The latter also provides an input voltage selector (60V-130 V / 140V-260 V).

They feature different protections to ensure output signal integrity: protections against overvoltage (255 V), overheating (95°) or overload (23 A). If one of these values is exceeded, units automatically go off and emit an acoustic signal, indicating it on the display. In addition, a switch allows the selection of output voltage (1% or 3%).

To avoid noises coming from ON/OFF switch, these devices feature a time delay circuit (3 or 6 sec.). After this time, normal operating mode starts automatically. A large display shows the information regarding devices status, like input, output and current voltage.



Additional outputs (AC 110V).
Only for EST 519/2.



Input voltage selector (60-130V / 140-260V).
Only for EST 519/2.

FEATURES

- Main supply: AC 140-250 V.
- Maximum joint load: 22 A.
- Maximum output current: 23 A.
- Time delay: 3 or 6 sec.
- Output voltage precision: 1% or 3%.
- Protections:
 - Overvoltage (255 V).
 - Overheat (95°).
 - Overload (23 A).
- Dimensions (WxHxD):
 - ESD 5 K/2: 230 x 220 x 370 mm.
 - EST 519/2: 483 x 185 x 340 mm.
- Weight:
 - ESD 5 K/2: 16.3 kg.
 - EST 519/2: 17 kg.

REAR PANEL



EST 519/2



ESD 5K/2



ESD 10 K

Voltage regulator

ESD 10 K is a voltage regulator that maintains a constant output supply when voltage oscillates between 140 and 250 V (with 220 V devices) or between 60 and 130 V (with 110V devices). It is possible to connect a 10 kVA fix load. As many fixtures performance depends on voltage, it is essential to ensure the regulation and control on these values.

Regarding inputs, it features a male CEE connector with 32 A and 3 poles, with 2 schuko connectors (one for 110V-10A and another for 230V-16 A) or terminals.

It features different protections to ensure output signal integrity: protections against overvoltage (255 V), overheat (95°) or overload. If one of these values is exceed, units automatically go off and emit an acoustic signal, indicating it on the display.


It also has double circuit breaker (63 A) on front panel and a switch for output voltage selection (1% or 3%).

To avoid noises coming from the interrupter, **ESD 10K** features a time delay circuit (3 or 6 sec.). After this time, normal operating mode starts automatically. Two large displays show the information regarding devices status, like input, output and current voltage.

FEATURES

- Main supply: AC 140-250 V.
- Maximum joint load: 10 KVA.
- Time delay: 3 or 6 sec.
- Output voltage precision: 1% or 3%.
- Protections:
 - Overvoltage (255 V).
 - Overheat (95°).
 - Overload.
- Dimensions (WxHxD): 305 x 260 x 460 mm.

REAR PANEL



In addition to 220 V outputs, it also features a 110 V output.



Main supply with protection lid and output voltage selector.



WPD 163-B

Power distributor




Rear panel of this power distributor designed in a 19" rack format features a 16 A tri-phase connector (3P+N+T) and 6 schuko connectors for output (2 per

phase) with security lid. Front panel has three additional schuko connectors (1 per phase) and 16 A circuit breakers.

WPD 323-B

Power distributor




As a versatile device, **WPD 323-B** allows many connections. It features a 32 A tri-phase input connector (3P+N+T) for three triple mono-phase outputs, each one accessible

with two 16 A CEE mono-phase connectors, schuko connectors or multi-connectors (3 phases connected to 2 multi-connectors in parallel mode). Circuit breakers for all the outputs ensure maximum protection.

WPD 1253-B

Power distributor



WPD 163-B

REAR PANEL



FEATURES

- Tri-phase power distributor (3x16 A input).
- 6 schuko connectors (2 per phase) with protection lid on rear panel.
- 3 additional schuko connectors on front panel (1 per phase) and 16 A circuit breakers (1 per phase).
- Dimensions: 2U rack units.

WPD 323-B

FEATURES

- Tri-phase power distributor (3x32 A input).
- Input with 32 A CEE connector (3P+N+T).
- 3 schuko connectors with protection lid (1 per phase) on rear panel.
- 2 x 16 A harting connectors (16 pins).
- 5 x 16 A circuit breakers for each phase.
- Dimensions: 5U rack units.

REAR PANEL



WPD 1253-B

WPD 1253-B is the most powerful power distributor of the WPD series.

Its tri-phase input connector (3P+N+T) allows operating on high level currents (125 A). It features 4 tri-phase outputs

with up to 63 A per phase. If output total is equal to 3x125A (input), it is possible to use 2 63 A outputs (full capacity) or 4 x 32 A outputs (x3).

REAR PANEL



FEATURES

- Tri-phase power distributor (3x125 A input).
- Input with 125 A CEE connector (3P+N+T).
- 4 x 64 A CEE connector (3P+N+T) with protection lid.
- Triple circuit breakers of 63 A on each output.
- 4x32 A circuit breakers for residual current.
- Dimensions: 5U rack units.



WPD 163

Power distributor



This power distributor designed in a 19" rack format features a 16 A tri-phase connector (3P+N+T) and 6 schuko connectors for output (16A each). It also has a protection circuit-breaker on each phase and an additional schuko connector for auxiliary supply. For a visualization of levels, **WPD 163** provides digital voltmeter and amp-meter for each phase.

WPD 323

Power distributor



This power distributor designed in a 19" rack format features a 32 A tri-phase connector (3P+N+T) and 6 schuko connectors for output (16 A each). It also has a protection circuit-breaker on each phase, other circuit breaker for residual currents and a 32 A CEE output connector for auxiliary supply.

For a visualization of levels, **WPD 323** provides digital voltmeter and amp-meter for each phase.

WPD 633

Power distributor



This power distributor designed in a 19" rack format features a 63 A tri-phase connector (3P+N+T) and 4 32 A CEE connectors for output (16 A each). It also has a protection circuit-breaker on each phase and other circuit breaker for residual currents.

For a visualization of levels, **WPD 323** provides digital voltmeter and amp-meter for each phase.

WPD 163

REAR PANEL



FEATURES

- Tri-phase power distributor (3x16 A per input).
- 6 x 16 A schuko connectors (2 per phase).
- Additional schuko connector for auxiliary supply.
- Digital voltmeter and amp-meter for each phase.
- Protection circuit-breaker on each phase.
- Dimensions (WxHxD): 483 x 88 x 210 mm.
- Weight: 3.8 kg.

WPD 323

REAR PANEL



FEATURES

- Tri-phase power distributor (3x32 A per input).
- 6 x 16 A schuko connectors (2 per phase).
- 32 A CEE output connector for auxiliary supply.
- Digital voltmeter and amp-meter for each phase.
- Protection circuit-breaker on each phase.
- Additional circuit breaker for residual current Fi 32 A 4 pole 0.03A.
- Dimensions (WxHxD): 483 x 132 x 265 mm.
- Weight: 7 kg.

WPD 633



Connector (included).

REAR PANEL



FEATURES

- Tri-phase power distributor (3x63 A per input).
- 4 x 32 A CEE output connectors (5p, 6h, 400V).
- Digital voltmeter and amp-meter for each phase.
- Protection circuit-breaker on each phase.
- Additional circuit breaker for residual current Fi 63 A 4 pole 0.03 A.
- Dimensions (WxHxD): 483 x 132 x 267 mm.
- Weight: 9.5 kg.



POWER SPLITTER

Power distributor



- Power splitter with phase separation.
- Power input: 380 V with CEE connector (3P+N+E).
 - 6 schuko outputs with phase indicator.
 - Dimensions: 220 x 150 x 102 mm.
 - Weight: 1.8 kg.

PD 61 SC

Power distributor



- Power splitter.
- 6 schuko outputs.
 - Dimensions: 350 x 150 x 102 mm.
 - Weight: 1.6 kg.

PD 81 S

Power distributor



- Power splitter.
- Power splitter with 8 schuko outputs and a 16 pin multi-connector for power input.
 - Dimensions (WxHxD): 345 x 150x 102 mm.
 - Weight: 3.2 kg.

PD 82 S

Power distributor



- Power splitter.
- Power input: multi-connector with 16 pin, for power input and link.
 - 6 schuko outputs and 1 multi-connector output.
 - Dimensions: 352 x 150 x 102 mm.
 - Weight: 3.5 kg.

PD 81 E

Power distributor



- Power splitter.
- Power input with 16 pins multi-connector.
 - 8 CEE (1P+N+E) outputs.
 - Dimensions: 382 x 170 x 123 mm.
 - Weight: 3.2 kg.

PD 82 E


Power distributor



- Power splitter.
- Power input and link with 16 pins multi-connectors.
 - 8 CEE (1P+N+E) outputs.
 - Dimensions: 385 x 170 x 127 mm.
 - Weight: 3.6 kg.

POWER SPLITTER 16.

This is a 16 A tri-phase power distribution box. It features link inputs and outputs with CEE connectors (5 pins) and 5 direct outputs with schuko connectors with protection lid. Each phase (2 schukos of 16 A) has circuit breakers that protect fixtures against any problems.



Internal wiring: connection scheme.

POWER SPLITTER 16


Tri-phase power distribution box



TECHNICAL DATA	POWER SPLITTER 16
Main power:	AC 230 V, 16 A 50/60 Hz.
Input connector:	Multi-connector, Male CEE, 3x16 A.
Max. load:	16 A (max) / phase.
Output connection:	6 x schuko + 1 female CEE connector (link).
Circuit breakers:	3 x 16 A.
Dimensions (WxHxD):	367 x 150 x 107 mm.
Weight:	2 kg.

POWER SPLITTER 32.

This is a 32 A tri-phase power distribution box. It features link inputs and outputs with CEE connectors (32 A, 5 pins) and 6 direct outputs with schuko connectors with protection lid. Each phase has 16A circuit breakers that protect fixtures against any problems.



Internal wiring: connection scheme.

POWER SPLITTER 32

Tri-phase power distribution box



TECHNICAL DATA	POWER SPLITTER 32
Main power:	AC 230 V, 32 A 50/60 Hz.
Input connector:	Multi-connector, Male CEE, 3x32 A.
Carga:	32 A (max) / phase.
Output connection:	6 x schuko + 1 female CEE connector (link)
Magnetotérmico:	6 x 16 A.
Dimensions (WxHxD):	460 x 150 x 112 mm.
Weight:	3.2 kg.



BPD 161 SC

Connection bar

- Connection bar with 6 schuko outputs.
- Tri-phase input with CEE 3x16 A connector (3P+N+E).
 - With hanging rings.
 - Dimensions (WxHxD): 490 x 150 x 120 mm.
 - Weight: 2 kg.



BPD 262 SC

Connection bar

- Connection bar with 6 schuko outputs.
- Tri-phase input and output with CEE 3 x 16 A connectors (3P+N+E).
 - With hanging rings.
 - Dimensions (WxHxD): 570 x 150 x 120 mm.
 - Weight: 2.50 kg.



BPD 161 E

Connection bar

- Connection bar with 6 outputs through 16 A monophas CEE connectors.
- Tri-phase input with CEE 3x16 A connector (3P+N+E).
 - With hanging rings.
 - Dimensions (WxHxD): 570 x 150 x 120 mm.
 - Weight: 2 kg.



BPD 262 E

Connection bar

- Connection bar with 6 outputs through 16 A monophas (1P+N+E) CEE connectors.
- Tri-phase input and output with CEE 3 x 16 A connectors (3P+N+E).
 - With hanging rings.
 - Dimensions (WxHxD): 695 x 150 x 120 mm.
 - Weight: 2.5 kg.



BPD 661

Connection bar

- Connection bar with 6 schuko outputs.
- Input through 16 pins multi-connector.
 - With hanging rings.
 - Dimensions (WxHxD): 510 x 150 x 95 mm.
 - Weight: 2 kg.



BPD 662

Connection bar

- Connection bar with 6 schuko outputs.
- Input and output through 16 pins multi-connector.
 - With hanging rings.
 - Dimensions (WxHxD): 606 x 100 x 70 mm.
 - Weight: 2.5 kg.



PP SCK 6

Rack-mount panel




Rack-mount panel with 6 schuko (16 A) outputs for power distribution.

It is possible to fix numbered plates between connectors for an easy identification of cables.

PP CEE 15

Rack-mount panel



Rack-mount panel with 6 CEE (1P+N+E) 16 A outputs for power distribution.

It is possible to fix numbered plates between connectors for an easy identification of cables.

These two electrical bars have a power connection interface and another for DMX signal. Its input and link multi-connectors distribute power between the schuko connectors (4 or 6 depending on the model). Thus, using DMX input connection, it is possible to send effects on each channel (via signal). Its hanging wings allows their location on structures or ceilings.

BAR 6200 DMX

BAR 4150 DMX

Electrical bars

DMX



BAR 4150 DMX

BAR 6200 DMX



TECHNICAL DATA	BAR 4150 DMX	BAR 6200 DMX
Number of channels:	4.	6.
Maximum load. per channel:	16 A.	16 A.
Multi-connector (IN/Link-OUT):	16 pin (16 A x pin).	16 pin (16 A x pin).
Dimensions (WxHxD):	1500 x 153 x 50 mm.	2000 x 153 x 50 mm.
Weight:	4.2 kg.	5.5 kg.



NC 100

Patch panel

Patch panel with 10 channels. Output sockets in rear panel. 5 A for each channel. 16 A total load. Fuses on front panel. Dimensions: 483 x 132 x 50 mm. Weight: 1.1 kg.



NC 100 F

Patch panel

Patch panel with 10 channels. Output sockets in rear panel. 5A for each channel. 16 A total load. Fuses on front panel. Flash button. Dimensions: 483 x 132 x 50 mm. Weight: 1.2 kg.



NC 600

Patch panel

Patch panel with 6 channels. Schuko outputs in rear panel. 5 A for each channel. 16 A total load. Fuses on front panel.

Dimensions: 483 x 88 x 150 mm. Weight: 2.1 kg.



REAR PANEL



NC 800

Patch panel

Patch panel with 8 channels. Schuko outputs in rear panel. 5 A for each channel. 16 A total load. Fuses on front panel.

Dimensions: 483 x 88 x 150 mm. Weight: 2.3 kg.



REAR PANEL



NC 1000

Patch panel

Patch panel with 10 channels. Schuko outputs in rear panel. 5 A in each channel. 16A total load. Fuses on front panel.

Dimensions: 483 x 132 x 150 mm. Weight: 3.2 kg.



REAR PANEL



NC 1000 F

Patch panel

Patch panel with 10 channels. Schuko outputs in rear panel. 5 A for each channel. 16 A total load. Fuses on front panel. Flash button.

Dimensions: 483 x 132 x 150 mm. Weight: 3.5 kg.



REAR PANEL





VMX 4

Audio/video multiplexer

REAR PANEL




Over the last years, video in performing events has become more important than ever. Now almost any small/medium event companies use video products in their shows, but media servers are cost expensive.

When users want to use a Media Server many video inputs, they need more powerful machines and more efficient graphic cards. Some applications only need switching but only one light/video operator (e.g. discotheques or small band performances).

VMX 4 is a Video Switcher with fade and controlled by DMX. Using it with their lighting console, users can now control: lights, media servers, external video inputs to these media servers (without increasing the cost of the media server hardware).

FEATURES


- 4 inputs for composite videos + stereo audio.
- DMX address selection using keyboard + LCD display.
- Video/audio input selection using DMX signal or manual mode with push buttons on front panel.
- Indicator on front panel for the selected input.
- 1U rack enclosure.
- Input switching using the first DMX channel from the selected address with the following intervals:
 - CH 1 : between 0 and 40.
 - CH 2 : between 60 and 100.8.
 - CH 3 : between 120 and 160.
- Fade time selection using the second DMX channel from the selected address.





PUZZLED PRO

Video LED panel



PUZZLED PRO has been designed to create spectacular screen effects in fixed and mobile installations. Each panel includes 25 high intensity RGB LEDs and it is controlled by software or DMX. Combination of panels allows playing pictures, videos and flash animations (.swf). All these media and can be played together to create new effects.


Framework of **PUZZLED PRO** is made of polycarbonate, probably the most adequate solution for this kind of fixtures.


FEATURES

- Distance between pixels: 40 mm.
- Frontal FROST acrylic filter.
- Supports BMP, JPG, AVI, WMV, MPEG, MPG, MOV, MPEG2, MPA, MPE and FLASH files.
- Control by DMX or using software (75 DMX channels per panel).
- 25 pixels per panel.

TECHNICAL DATA	PUZZLED PRO
Colour range:	16.700.000 (24 bit).
Pixel density:	625 pixels/m ² .
Light source:	25 SMD RGB LEDs. with high intensity.
Lifetime:	50.000 hours.
Main supply:	DC 24 V.
LED type:	SMD.
Power consumption:	4W (170 mA).
Wave length:	625 (R) / 525 (G) / 465 (B) nm.
Light intensity (6.87m):	520 cd/m ² .
Beam angle:	120°.
Protocol:	DMX 512.
Connection:	Terminal.
Operating temperature:	-10° C ~ +50° C.
Dimensions (WxHxD):	200 x 200 x 37 mm.
Weight:	800 g.


	LUX	SIZE (mm.)	LUX	SIZE (mm.)	LUX	SIZE (mm.)	LUX	SIZE (mm.)
RED	6.2	1290	1.6	25800	0.6	3860	0.2	6450
GREEN	8.4	1280	2.2	2560	1.0	3840	0.4	6400
BLUE	3.8	1305	1.0	2605	0.4	3905	0.2	6510
WHITE	16.8	1300	4.2	2600	1.8	3900	0.6	6500





PUZZLED PRO

SYSTEM CONFIGURATION



216 PUZZLED PRO matrix configuration, using DMX-NET 8 and 1000 K proprietary protocol (1 M). Each of the 8 output universes provides 2025 control channels (total: 16200 DMX channels).




PUZZLED PCB PRO VIDEO

PUZZLED PCB VIDEO

VIDEO WALL PCB

Video LED panels



PUZZLED PCB VIDEO



PUZZLED PCB PRO VIDEO

NEW

This range of LED panels has been designed for video animation. The three models take advantage of the SMD technology that generates colour from a unique point, creating a natural chromatic tone.

Essential fixtures for lighting designers.

These panels can be used as background and they perfectly integrate themselves in any kind of installations: theatre stages, TV studios, macro discotheques, touring, etc.

Each fixture has its own dimensions so lighting designers can design structures according to their needs. For an easy installation, a mounting accessory (made of ABS plastic) connects panels together and can be deformed to create forms like curves, squares, etc. Pixel quantity per channel and distance between them will determine definition of final image.


Total control on fixtures.

Each pixel is controlled by 3 DMX channels (one per colour). This allows using video controllers or even DMX recorders. Automatic DMX addressing is another advantage of these fixtures, as there is no waste of time for individual configuration of panels.


All these units support DMX 512 signals and DMX 1000K (proprietary high speed protocol / 1M). They perfectly work with mapper software and LED video converters (e.g. DMX-NET 8).

TECHNICAL DATA	PUZZLED PCB VIDEO	PUZZLED PCB PRO VIDEO	VIDEO WALL PCB
Colour range:	16.7000.000 (24bit).	16.700.000 (24 bit).	16.700.000 (24 bit).
Distance between pixels:	63.5 mm.	40 mm.	25 mm.
LED quantity:	16 RGB SMD LEDs .	25 RGB SMD LEDs	96 RGB SMD LEDs.
Lifetime:	50000 h.	50.000 h.	50.000 h.
Main supply:	DC 24V.	DC 24V.	DC 24V.
Power consumption:	6 W.	9.6 W.	25 W.
Beam angle:	120°.	120°.	120°.
Protocol:	DMX 512 / DMX 1000K (1M).	DMX 512 / DMX 1000K (1M).	DMX 512 / DMX 1000K (1M).
Control capacity:	48 DMX channels.	75 DMX channels.	288 DMX channels.
Dimensions:	203 x 203 x 15 mm.	175 x 175 x 10 mm.	391 x 133 x 7 mm.
Weight:	120 g.	120 g.	120 g.


NEW




VIDEO WALL PCB




VIDEO WALL PCB



PUZZLED PCB VIDEO



PUZZLED PCB PRO VIDEO



Installation of 50x25 pixels of PUZZLED PCB PRO VIDEO using the 8 outputs of DMX NET 8 and ArKaos control software.



LED LINE VIDEO

SMD RGB LED strip

NEW




TECHNICAL DATA	LED LINE VIDEO
Colour range:	16.700.000 (24 bit).
Number of pixels:	10 per strip.
Distance between pixels:	40 mm.
Light source:	10 RGB LEDs (SMD).
Main Supply:	DC 5 V.
Power consumption:	2.5 W.
Beam angle:	120°.
Protocol:	DMX 512.
Housing:	Polycarbonate with UV stabilizer.
Operating temperature:	- 10° + 50° C.
Dimensions (WxHxD):	400 x 13 x 7 mm.
Weight:	30 g.

With its pixels clearly defined, **LED LINE VIDEO** strips allow designing lighting screens to visualize colours, forms, images, moving text or even video animations.

It is composed of 10 SMD RGB LEDs that emit colour mixing form a unique point to get a great colour definition with low power requirements.

Design of **LED LINE VIDEO** provides maximum flexibility to create strip matrices. Thanks to their lightweight and thickness, they are easily placed on walls creating impressive backgrounds. Associated to a DMX programming, they are optimized to show all kind of video effects. They result particularly appropriate for night clubs, TV studios or even interior design.



Please see pg. 86 for driver and control selection.


Luminosity


COLOUR	1m		2m		3m		5m	
	Lux	Dim. (mm)	Lux	Dim. (mm)	Lux	Dim. (mm)	Lux	Dim. (mm)
RED	5.6	1310	1.4	2620	0.6	3930	0.2	6550
GREEN	9	1396	2.2	2792	1.0	4188	0.4	6380
BLUE	2.6	1340	0.6	2680	0.2	4020		
WHITE	16.8	1384	4.2	2768	1.8	4152	0.6	6320

Output

COLOUR	Total (lumens)	POWER (W)	Efficiency (lm/W)
RED	17.27	1.1	15.7
GREEN	30.50	1.4	21.78
BLUE	8.29	1.4	5.79
WHITE	55.02	3.4	16.18

Total intensity in white colour.





This is the LED driver designed for **LED LINE VIDEO**. Its main function is the automatic DMX addressing, with up to 180 channels. One **MINI VIDEO DRIVER** can control up to 60 pixels of **LED LINE VIDEO** (600 using DMX 1000K protocol).

MINI VIDEO DRIVER

LED Driver

TECHNICAL DATA	MINI VIDEO DRIVER
Main Supply:	DC 5 V.
Power consumption:	3 A max.
Protocol:	DMX 512 /DMX-1000K (1M).
Dimensions (WxHxD):	79.6 x 40 x 16.8 mm.
Weight:	70 g.



NEW

LED FIXTURES



VIDEO TUBE


SMD RGB LED tube

65
IP

NEW

This tube with reduced diameter features SMD RGB LEDs. Two dimensions are available: 60 or 120 cm. **VIDEO TUBE** supports video and picture signals, creating attractive lighting matrices. Thanks to its high IP range (IP 65), these tubes can be used for outdoor installations.

Connection between **VIDEO TUBE** fixtures is really easy, as they directly connect themselves, without any cable or other accessory. Its controller, **VIDEO TUBE DRIVER**, allows the visualization of strips up to 200 pixels (between 6 or 12 units depending on model).



Please see pg. 86 for driver and control selection.

VT 600 (600mm)
VT 1200 (1200mm)

TECHNICAL DATA	VIDEO TUBE
Colour range:	16.700.000 (24 bit).
Distance between pixels:	40 mm.
LED quantity:	15 (VT 600) 30 (VT 1200).
Lifetime:	50.000 h.
Main Supply:	DC 5 V.
Power consumption:	4 W (VT 600) 8 W (VT 1200).
Brightness:	915 cd/m ² .
Beam angle:	120°.
Protocol:	DMX 512 /1000 K(1M).
IP range:	IP 65.
Housing:	Polycarbonate with UV stabilizer.
Operating temperature:	0° + 50°C.
Dimensions:	600 x Ø 20 mm. (VT 600). 1200 X Ø 20 mm. (VT 1200).
Weight:	130 g. (VT 600) 210 g. (VT 1200).

65
IP

VIDEO TUBE DRIVER IP

Driver for VIDEO TUBE series

NEW



VIDEO TUBE DRIVER IP is a driver designed for **VIDEO TUBE** control. It elevate IP range (IP 65) turns it into a useful device for outdoor installations.

DMX addressing and channels are automatically assigned and pixel value is perfectly controllable by user. The device is compatible with DMX 512 and DMX 1000K (proprietary protocol) protocols. A LCD display shows DMX starting value.

With **VIDEO TUBE DRIVER IP**, user can control up to 11 **VT 600** and 5 **VT 1200**, using DMX 512 protocol (up to 40 **VT 600** and 20 **VT 1200** using the 1000K proprietary protocol).



TECHNICAL DATA	VIDEO TUBE DRIVER IP
Main Supply:	AC 100-240 V.
Power consumption:	1.8 A max.
IP range:	IP 65.
Control protocol:	DMX 512 or DMX-1000K (proprietary protocol).
Dimensions (WxHxD):	163 x 112 x 39 mm.
Weight:	1.25 kg.



NEW

JB 2

Signal/supply adapter

JB 2 is a new device that supplies and sends DMX signal to an installation using **VIDEO TUBE**. It has separate DMX signals and POWERCON connector.

A standard 8pin output connector (with both supply and signal) allows its connection with **VIDEO TUBE DRIVER IP**. Each **JB 2** can supply up to 3 **VIDEO TUBE DRIVER IP** for an easy connection and distribution of signals and supply.

TECHNICAL DATA	JB 2
Main supply:	AC 230 V 50 Hz.
Power consumption:	10 A max.
Input:	XLR3 (DMX). POWERCON supply.
Output:	Connect 8 pin (IP 67).
Housing:	Aluminium.
IP range:	IP 20.
Operating temperature:	-10° + 50°C.
Dimensions (WxHxD):	110 x 68 X 43 mm.
Weight:	250 g.





PUZZLED PCB

SMD RGB LED panel

DMX

DIRECT
DMX
INPUT




This 16 SMD RGB LED panel does not require any controller. Easy to install, compact and powerful, this innovative concept is particularly adapted to nightclubs, TV studios, casinos or architectural lighting applications.

Designed for largest installations, this unique system creates spectacular effects using a DMX program and configuring lighting display. Software control allows the conversion of video signals into 48 DMX universes.


All the parameters and functions of **PUZZLED PCB** can be programmed through XB-R1 (device not included) that identifies each unit separately inside the network. **PUZZLED PCB** can work in DMX mode, Autonomous mode or Master/Slave mode.

System configuration.



TECHNICAL DATA	PUZZLED PCB
Colour range:	16.700.000 (24bit).
Distance between pixels:	50 mm.
Light source:	16 SMD RGB LEDs.
Lifetime:	50.000 hours.
Operating voltage:	DC 24 V.
LED type:	SMD RGB.
Power consumption:	4W (170mA).
Wave length:	629(R)/522(G)/472(B) nm.
Light intensity (6.87m):	15.09 (lm).
Beam angle:	120°.
Control:	DMX 512.
Connection:	Terminal 6 pin.
Operating temperature:	-10° C ~ +50° C.
Dimensions (WxHxD):	165 x 165 x 15 mm.
Weight:	80 g.

Mounting kit.



XB-R1

This device configures DMX address and operating modes of **PUZZLED PCB** (not included).



DMX PATCHER

This is an economic solution for **PUZZLED PCB** units addressing.





NEW

APU 604

60x60 cm LED panel (4000° K).


APU 605

60x60 cm LED panel (6000° K).

APU 604 and **APU 605** are two 60 cm square panels that emit white light. The only difference between both panels comes from their colour temperature.

Lambertian reflection provides a uniform light intensity distribution over the entire surface, offering the same brightness on each point of the panel.

APU 604 and **APU 605** are very easy to install, as they feature standard dimensions and do not require any controller. They are particularly appropriate for offices, conference meeting rooms, halls, etc. as they perfectly simulate natural light.



Emission and intensity angles for APU 604 and APU 605 panels.



TECHNICAL DATA	APU 604	APU 605
Colour temperature:	4000° K.	6000° K.
Light intensity:	2500 lm.	2500 lm.
Operating temperature:	-20° a + 45°C.	-20° a + 45°C.
Main supply:	AC 110 – 240 V.	AC 110 – 240 V.
Power consumption:	65 W.	65 W.
Dimensions (WxHxD):	600 x 600 x 12 mm.	600 x 600 x 12 mm.



LED LINE 200 IP

65
IP

SMD RGB LED strip

NEW


This 336 mm LED strip featuring 14 SMD RGB LEDs takes advantage of the SMD technology that generates colour from a unique point, creating a natural chromatic tone. Inserted in a transparent capsule of silicon resin, it can be used for both indoor and outdoor applications. An aluminium profile ensures its reliability.

Due to its dimensions and its IP range (IP 65), LED LINE 200 IP is suitable for many applications: fixed stages, theatres, corridors, museums, outdoor signalization, etc.

Please see pg. 86 for driver and control selection.




TECHNICAL DATA	LED LINE 200 IP
Light source:	14 SMD RGB LEDs.
Colour range:	16.700.000 (24 bit).
Distance between pixels:	21.4 mm.
Lifetime:	50.000 h.
Main supply:	DC 24 V.
Power consumption:	3.4 W max.
Wave length:	622/630 (R), 524/523 (G), 464/472 (B) nm.
Beam angle:	120°.
Protocol:	DMX 512 .
IP range:	IP 65.
Light intensity:	430 (R), 1000 (G), 230 (B) mcd.
Operating temperature:	0° + 50°C.
Dimensions:	336 x 21 x 9 mm.
Weight:	77 g.



LED LINE 10

RGB LED strip



LED LINE 10 is a strip with LEDs grouped in RGB nodes. Due to LEDs high density, colour is totally uniform.

Lighting designers can take advantage of the reduced size of this device, as it allows installing it in any walls, curves and angles. It creates different atmospheres on punctual spaces or background stages using a matrix of **LED LINE 10** units.

Please see pg. 86 for driver and control selection.

TECHNICAL DATA	LED LINE 10
Main supply:	DC 24 V.
LED quantity:	15 LEDs (5R, 5G, 5B).
Beam angle:	120°.
Light intensity:	15.09 lm.
Wave length:	625 (R), 525 (G), 465 (B) nm.
Power consumption:	1.5 W (60 mA).
Connection:	Terminals.
Dimensions (WxHxD):	100 x 16 x 19.5 mm.
Weight:	10.8 g.



LD5 RGB

5W RGB LED lamp

NEW

LD5 CONTROLLER



Remote control.



LD5 RGB


Thanks to its RGB LED of 5W, **LD5 RGB** creates from a unique point a natural chromatic tone. Its front filter reduces dispersion to reach an important intensity level over the lighting area.

Its MR-16 type lamp socket allows placing it in existing halogen lamp installations. It perfectly integrates itself in corridors, display cases, event rooms, etc.

LD5 CONTROLLER is the driver for **LD5-RGB** control. Featuring four channels, it synchronizes up to 100 units per channel and provides the functions required for a total control on lighting. **LD SPLITTER** ensures the connection between **LD5-RGB** lamps.

LDR-RGB also includes a remote control that allows changing colours and triggering sequences. This is very convenient to change lighting in different areas at the same time and from the same place. Thus, user can select 7 chromatic tones (primary colours and their mixes) and adjust intensity level of each one to get the tone he wants. There are 5 operating modes for colour change: white colour strobe, smooth fade, flash effect, sequences synchronized by audio with speed and fade time adjustment.

LD5 RGB CONNECTION USING LD SPLITTER.



LD5 RGB system allows the connection of up to 100 lamps at each port of the controller (LD5 CONTROLLER). It requires LD SPLITTER (connection of 8 lamps with input and output signal to increase the system).



1 m extension cable to connect LD5 RGB and LD SPLITTER together (included with the lamp)



TECHNICAL DATA	LD5 RGB
LED quantity:	1 x 5W LEDs (R, G, B).
Lamp socket:	MR16.
Beam angle:	35°.
Lifetime:	50.000 hours.
Main supply:	AC 12 V.
Dimensions:	49 mm. x Ø 47 mm.
Weight:	30 g.

LD SPLITTER



Splitter required for the connection of 8 lamps. Input and output signal to connect the controller to other LD SPLITTER (up to 100 lamps per port).

TECHNICAL DATA	LD5 CONTROLLER
Main supply:	AC 230V 50 Hz. / AC 12 V. (power supply included).
Output:	4.
Max capacity per port:	100 LD5 RGB.
Colours:	7 (primary colours + combination).
Flash function:	Included (with speed control).
Dimensions:	112 x 128 x 28 mm.
Weight:	75 g.



DECOLED RGB

3W RGB LED spot

Please see pg. 86 for driver and control selection.



DECOLED RGB associates the chassis of the successful Minimultipar spot with LED technology: it becomes possible to control colour and intensity through DMX signal (thanks to **DECOLED CONTROLLER**). Each unit features 3 high intensity RGB LEDs (1W) that can be independently dimerized to achieve the desired colour. Thanks to its modern design, it easily integrates itself in any place.

TECHNICAL DATA	DECOLED RGB
Light source:	3 high intensity RGB LEDs (1W).
Available colours:	Black, Zinc plate and White.
Dimensions:	170 x 90 x 110 mm.

DECOLED CONTROLLER

LED fixture controller



DECOLED CONTROLLER is the supply and control unit for **DECOLED RGB** fixtures.

It provides many operating modes: Manual with individual adjustment of RGB level and dimmer for the 7 integrated patterns, repeat triggering of the 7 integrated patterns, audio synchronization. User can control between 3 and 30 DMX channels to achieve the best combination between units.

TECHNICAL DATA	DECOLED CONTROLLER
Outputs:	10 outputs.
Maximum load:	3 W per output.
DMX control:	6 operating modes (between 3 and 30 DMX channels).
Main supply:	AC 230 V 50 Hz.
Power consumption:	75 W.
Dimensions (WxHxD):	470 x 145 x 48 mm.
Weight:	3.5 kg.

DECOLED WHITE 3K

DECOLED WHITE 6K

3000°/6000° LED spots



DECOLED WHITE 3K



DECOLED WHITE 6K

Efficient **DECOLED WHITE** projectors integrate a driver for LED supply. They provide high light intensity and low power consumption, replacing thus conventional projectors. They feature cable with schuko connectors and filter frame.

The only difference between both panels comes from their colour temperature, so user can choose the one that perfectly meets his needs.

TECHNICAL DATA	DECOLED WHITE 3K	DECOLED WHITE 6K
Beam angle:	25°.	25°.
LED type:	3x1 W.	3x1W.
Brightness:	3000° K.	6000° K.
Main supply:	AC 90- 260V 50 Hz/60 Hz.	AC 90- 260V 50 Hz/60 Hz.
Dimensions (WxHxD):	110 x 90 x 170 mm.	110 x 90 x 170 mm.
Weight:	0.55 kg.	0.55 kg.



MINIDIM 1

MINIDIM RGB

1/3 DMX channel drivers (6 A)

This series of compact LED drivers offers an interesting solution for control and configuration, being a great alternative to conventional dimmers that require many spaces.

Both devices are very compact dimmers that control loads up to 6 A. Their DMX interface allows unit interconnection to supply a complex LED network with a great autonomy in its operation. They adapt themselves to any input between 12 and 24 V.

MINIDIM 1

This 1 channel LED driver is perfectly adequate to white colour LED fixtures. It supports DMX inputs and outputs to link other units as 0-10 V analog signals. Two operating modes are available: starting address channel (DMX) and increasing percentage of output intensity (manual).

TECHNICAL DATA	MINIDIM 1
Number of channels:	1.
Maximum load:	6 A.
Control signal:	0-10 V Analog/DMX 512.
Connection:	Terminals.
Main supply:	DC 12-24 V 6.5 A max.
Dimensions:	86 x 40 x 15 mm.
Weight:	150 g.

MINIDIM 1




MINIDIM RGB

This is the 3 channel version of MINIDIM 1, designed for RGB LED strips. It also supports loads up to 6 A and its DMX interface allows linking units for an extended network. Two operating modes are available: starting address channel (DMX) and increasing percentage of output intensity (manual).

TECHNICAL DATA	MINIDIM RGB
Number of channels:	3.
Maximum load:	6 A.
Control signal:	DMX 512.
Connection:	Terminals.
Main supply:	DC 12-24 V 6.5 A max.
Dimensions:	86 x 50 x 15 mm.
Weight:	230 g.

MINIDIM RGB





MINIDIM RGB (DIN version)

RGB LED driver

NEW



This advanced version of **MINIDIM RGB** includes an additional channel for total dimmer. The other distinction is that it provides 8 programs with speed and brightness. Like **MINIDIM RGB**, it supports loads up to 6 A and its DMX interface allows linking units for an extended network.

Two operating modes are available: DMX start channel (DMX) and increasing percentage of output intensity (Manual).

TECHNICAL DATA	MINIDIM RGB (DIN version)
Number of channels:	3 + 1 (full dimmer).
Max. load:	6 A.
Control signal:	DMX 512.
Connexion:	Terminals.
Main supply:	DC 12-24 V 6.5 A max.
Dimensions (WxHxD):	66 x 84 x 30 mm.
Weight:	270 g.



Installation with two different zones controlled from and unique AR 6.



SLA series is suitable for DIN rails.

MINIDIM 8 (DIN version)


8 RGB channel LED driver

NEW



MINIDIM 8 is a RGB driver featuring eight outputs of 3 channels each. Several operating modes are available. Depending on it, outputs can be grouped in 25, 13, 7, 4, 2 or 1 DMX channels. This is particularly helpful because it increases possibilities to customize lighting installations: using **MINIDIM 8**, lighting designers can set the colour for each LED strip, taking advantage of 8 RGB outputs controlled through DMX signal.

TECHNICAL DATA	MINIDIM 8 (DIN version)
Number of channels:	1, 2, 4, 7, 13, 25 (depending on operating mode).
Max. load:	3 A per output.
Control signal:	DMX 512.
Connexion:	Terminals.
Main supply:	DC 12-24 V 6.5 A max.
Dimensions (WxHxD):	135 x 84 x 30 mm.
Weight:	650 g.



Installation with eight zones. Depending on operating mode, they can be grouped in different environments.



MULTILED CONTROLLER

3 channel DMX driver/controller

MULTILED CONTROLLER is a driver for LED strips with many functions and supporting important loads. It adapts itself to any input between 12 and 24 V. Its double output allows loading up to 5 A (per output) so large lighting installations can be controlled with a unique device.

There are three ways to control this device:

1. By **DMX signal**: control is made by 3 channels (R+B+G); DMX start address configurable by DIP switch.

2. By **remote controller** (Included): users can use it to access to different colours and chases.


3. Through **automatic modes**: The unit features 9 operating modes (configurable by DIP switch and selection buttons). These operating modes provide an individualized control of primary colours, colour loops and full RGB mix with fade time control.




FEATURES

- Controller/Driver for RGB LEDs.
- 2 outputs, each one supporting up to 5 A.
- 9 configurable operating modes.
- IR remote control.
- LED indicator for DMX presence and error.

TECHNICAL DATA	MULTILED CONTROLLER
Outputs:	2 RGB x 5 A (parallel).
DMX channels:	3 channels.
Operating modes:	9.
Main supply:	DC 9-24 V (10 A max.).
Dimensions:	125 x 115 x 40 mm.
Weight:	0.5 kg.





LM-4 POWER

DMX/Ethernet LED driver

NEW

ArtNet
COMPATIBLE



LM-4 Power is the first LED driver designed to work through Ethernet network. It associates in a unique device 2 powerful tools:

- LED driver through ArtNet.
- LED driver through DMX.



WEB SERVER for LM-4 POWER configuration. It is possible to edit IP address and unit description.

Advantages of such a combination are obvious, as it allows almost any RGB LED installations:

- In conventional lighting installations, by connecting a DMX console to **LM-4 Power** input (DMX mode, see scheme 1).
- In integrated lighting system installations working in an Ethernet network, with several DMX universes (ArtNet mode, see scheme 2).

Configuration of both DMX and ArtNet modes is very easy and allows saving many time in installation:

- Through DMX mode, user only has to indicate DMX start address.
- Through ArtNet mode, using DIP-switch to select Subnet mask and universe (as well as DMX start address).

LM-4 Power also stands out for the output power it can manage: indeed, it features independent colour channels divided in 2 RGB outputs of 15 A each (5 A per colour, max load of 30 A). Associated with its great control capabilities and its very small size, **LM-4 Power** can be considered as an adequate solution for any lighting installation.

Dimensions (WxHxD): 82 x 45 x 120 mm.




Front panel for LAN connection, group selector and LED for DMX and Ethernet signal




2 RGB outputs of 5 A per colour (total 30A). DIP switch for DMX address Net mask selection, depending on operating mode (DMX or ArtNet).

SCHEME 1



LM-4 POWER in an installation that receives direct DMX signal from a lighting console. Load power capacity of **LM-4 POWER** allows connecting up to 500 LED LINE 10 units.

SCHEME 2



LM-4 POWER in an installation with Ethernet network. The console sends signal to various universes through ArtNet protocol. 2 **LM-3R** units control moving heads and 1 **LM-4 POWER** controls a LED LINE matrix.



SUGGESTED CONTROLLERS DEPENDING ON LED FIXTURES

<p>LED CONTROL 3000 IR</p> 	<p>LED LINE 102</p>  <p>400 units: 50 per output (max: 25 per line).</p>	<p>LED LINE 300</p>  <p>320 units: 40 per output (max: 20 per line).</p>	
<p>LM-4 POWER</p>  <p>MULTILED CONTROLLER</p>  <p>MINIDIM RGB MINIDIM RGB (DIN version)</p>  <p>MINIDIM 8 (DIN version)</p> 	<p>LED LINE 200 IP</p>  <p>LM-4 POWER: 200 units (max: 25 per line). MULTILED CONTROLLER: 64 units (max: 32 per line). MINIDIM RGB: 440 units (max: 20 per line). MINIDIM 8: 20 units per output (Total 160 units).</p>	<p>LED LINE 10</p>  <p>LM-4 POWER: 500 units (max: 50 per line). MULTILED CONTROLLER: 160 units (max: 40 per line). MINIDIM RGB: 100 units (max: 50 per line). MINIDIM 8: 50 units per output (Total 400 units).</p>	<p>LED LINE 6</p>  <p>LM-4 POWER: 400 units (max: 40 per line). MULTILED CONTROLLER: 108 units (max: 54 per line). MINIDIM RGB: 100 units (max: 50 per line). MINIDIM 8: 40 units per output (Total 320 units).</p>
<p>WRN 1230</p>  <p>LM-4 POWER: 20 units (max: 5 per line). MULTILED CONTROLLER: 6 units (max: 2 per line). MINIDIM RGB: 4 units (max: 2 per line). MINIDIM 8: 2 units per output (Total 16 units).</p>	<p>WRN 1830</p>  <p>LM-4 POWER: 12 units (max: 3 per line). MULTILED CONTROLLER: 4 units (max: 2 per line). MINIDIM RGB: 3 units (max). MINIDIM 8: 1 unit per output (Total 8 units).</p>	<p>WBAR 1230</p>  <p>LM-4 POWER: 20 units (max: 5 per line). MULTILED CONTROLLER: 6 units (max: 2 per line). MINIDIM RGB: 4 units (max: 2 per line). MINIDIM 8: 2 units per output (Total 16 units).</p>	
<p>WBAR 1830</p>  <p>LM-4 POWER: 12 units (max: 3 per line). MULTILED CONTROLLER: 4 units (max: 2 per line). MINIDIM RGB: 3 units (max). MINIDIM 8: 1 unit per output (Total 8 units).</p>	<p>WBAR 2430</p>  <p>LM-4 POWER: 10 units (max: 3 per line). MULTILED CONTROLLER: 2 units (max). MINIDIM RGB: 2 units (max). MINIDIM 8: 1 unit per output (Total 8 units).</p>		
<p>VIDEO TUBE DRIVER IP</p>  <p>3 units (max) per distributor JB-2.</p>	<p>VIDEO TUBE 1200</p>  <p>5 units (max) through DMX 512 / 20 units (max) through DMX 1000 K (1 M).</p>	<p>VIDEO TUBE 600</p>  <p>11 units (max) through DMX 512 / 40 units (max) through DMX 1000 K (1 M).</p>	
<p>MINI VIDEO DRIVER</p> 	<p>LED LINE VIDEO</p>  <p>6 units (max) through DMX 512 / 60 units (max) through DMX 1000 K (1 M).</p>		
<p>DECOLED CONTROLLER</p> 	<p>DECOLED RGB</p>  <p>10 units (max).</p>	<p>LD5 CONTROLLER</p> 	<p>LD5 RGB</p>  <p>400 units (max: 100 per port / 4 ports). 1 LD SPLITTER (power unit) for 8 LD5 RGB.</p>



NEW

12/24V POWER SUPPLY

Power units for LED effects

This series of switch power supply allows the configuration of stable LED installations. Their internal circuitry provides a constant voltage. For maximum security, they all feature a cooling system and internal protections.

Four ranges of power supply are available, each one with specific power (100 W, 15 W, 200 W and 480 W) and output voltage (5 V, 12 V and 24 V). 100 W version is only available with 12 V.

TECHNICAL DATA		SP-480-12	SP-480-24	S-40-5
OUTPUT	Output voltage:	12 V.	24 V.	5 V.
	Current:	40 A.	20 A.	8 A.
	Power:	480 W.	480 W.	40 W.
	Voltage range:	10.8 - 13.2 V.	22 - 27.6 V.	4.75 - 5.5 V.
INPUT	Voltage range:	AC 85-264 V DC 120-370 V.	AC 85-264 V DC 120-370 V.	AC 85-264 V DC 120-370 V.
	Frequency range:	47 - 63 Hz.	47 - 63 Hz.	47 - 63 Hz.
	Power factor:	PF>0.95 / AC 230 V.	PF>0.95 / AC 230 V.	PF >0.95 / AC 230 V.
PROTECTIONS	Overload:	45.15 - 58.05 A.	23.1 - 29.7 A.	8.2 - 12 A.
	Overvoltage:	13.8 - 16.2 V.	28.8 - 33.6 V.	5.75 - 6.75 V.
	Overheat:	80°C (TSW1) 90°C (TSW2).	80°C (TSW1) 90°C (TSW2).	-----
	Dimensions:	278 x 127 x 43 mm.	278 x 127 x 43 mm.	129 x 98 x 38 mm.
	Weight:	1.7 kg.	1.7 kg.	0.44 kg.

TECHNICAL DATA		S-100-F-12	S-150-12	S-150-24
OUTPUT	Output voltage:	12 V.	12 V.	24 V.
	Current:	8.5 A.	12.5 A.	6.5 A.
	Power:	102 W.	150 W.	156 W.
	Voltage range:	11.4 - 13.2V.	10.6 - 13.2 V.	21 - 28 V.
INPUT	Voltage range:	AC 85-264 V DC 120-370 V.	AC 88-132 V DC 176-264 V selectable.	AC 88-132 V DC 176-264 V selectable.
	Frequency range:	47 - 63 Hz.	47 - 63 Hz	47 - 63 Hz.
PROTECTIONS	Overload:	105-150% power output.	105-150% power output.	105-150% power output.
	Overvoltage:	13.2 - 16.2 V.	13.8 - 16.2 V.	30 - 34.8 V.
	Dimensions:	199 x 98 x 38 mm.	199 x 110 x 50 mm.	179 x 110 x 50 mm.
	Weight:	0.66 kg.	0.8 kg.	0.8 kg.

TECHNICAL DATA		SP-200-12	SP-200-24
OUTPUT	Output voltage:	12 V.	24 V.
	Current:	16.7 A.	8.4 A.
	Power:	200.4 W.	201.6 W.
	Voltage range:	11.4 - 13.2 V.	22.8 - 26.4 V.
INPUT	Voltage range:	AC 85-264 V DC 120-370 V.	AC 85-264 V DC 120-370 V.
	Frequency range:	47 - 63 Hz.	47 - 63 Hz.
	Power factor:	PF>0.93/ AC 230 V.	PF>0.93/ AC 230 V.
PROTECTIONS	Overload:	105-150% power output.	105-150% power output.
	Overvoltage:	13.2 - 16.2 V.	26.4 - 32.4 V.
	Overheat:	95°C.	95°C.
	Dimensions:	199 x 99 x 50 mm.	199 x 99 x 50 mm.
	Weight:	0.85 kg.	0.85 kg.



WASHLIGHTS

LED RGB effects

65
IP



WBAR 1230

WBAR 1830

WBAR 2430

3W
THREE-COLOR LED




WBAR 1230



WBAR 1830



WBAR 2430



These 3 fixtures feature RGB LEDs built in a strong bar for its installation on walls and ceilings. Their housing with crystal cover makes possible their use in indoor and outdoor installations (they all have IP 65 range).

If the 3 models use the same supply (DC 24 V), each unit has its own number of LEDs with a precise power. Wash effect on front panel scatters the colour and provides a natural and uniform chromatic tone.

TECHNICAL DATA	WBAR 1230	WBAR 1830	WBAR 2430
LED quantity:	12 (RGB).	18 (RGB).	24 (RGB).
Individual LED consumption:	3 W.	3 W.	3 W.
Beam angle:	15°.	15°.	15°.
Main supply:	DC 24 V.	DC 24 V.	DC 24 V.
Control mode:	RGB.	RGB.	RGB.
Max. power consumption:	36 W.	54 W.	72 W.
Dimensions (WxHxD):	660 x 80 x 80 mm.	1000 x 80 x 80 mm.	1200 x 80 x 80 mm.
Weight:	2.8 kg.	3.5 kg.	4.2 kg.




KBR 100 1 meter.
KBR 200 2 meters.

WBAR 2430



Please see pg. 86 for driver and control selection.

Cables for interconnection between units and controller. It transports RGB signal and power supply. 2 available lengths: 1 or 2 meters.



Connection example with the 3 WASHBAR models using **MINIDIM RGB** drivers and **KBR** interconnection cables. Control from a lighting console (**SCAN 1000 DMX**).



WRN 1230

65
IP

WRN 1830

65
IP

RGB LED WASH projectors


3W
THREE-COLOR LED

WRN 1230

WRN 1830

NEW

WRN series are fixtures with RGB LEDs and designed in a round housing. It offers many possibilities for architectural applications: wall painting, specific focus on one direction, building entrances, etc.

Its aluminium housing with crystal cover makes possible its use in indoor and outdoor installations (they all have IP 65 range).

Number of 3 W LEDs changes depending on the model (12 for **WRN 1230** and 18 for **WRN 1830**). Each LED has a WASH type lens that scatters the colour and provides a natural and uniform chromatic tone.

There are many way to fix them: on walls, ceilings, floors or any furniture. In addition, the strong base of these units allows turning the optical element at 180°.

Please see pg. 86 for driver and control selection.



Connection example with WRN projectors using MINIDIM RGB and KBR interconnection cables. Control from a lighting console (SCAN 1000 DMX).

KBR 100 1 meter.
KBR 200 2 meters.



Cables for interconnection between units and controller. It transports RGB signal and power supply. 2 available lengths: 1 or 2 meters.

TECHNICAL DATA	WRN 1230	WRN 1830
LED quantity:	12 (RGB).	18 (RGB).
Individual LED consumption:	3 W (tri-colour).	3 W (tri-colour).
Beam angle:	35°.	35°.
Main supply:	DC 24 V.	DC 24 V.
Control mode:	RGB.	RGB.
Max. power consumption:	36 W.	54 W.
Dimensions:	265 x 315 x240 mm.	265 x 315 x 240 mm.
Weight:	3.8 kg.	3.8 kg.



FLOODLED PRO IP

65
IP

45W RGB LED projector



NEW



DMX

TECHNICAL DATA	FLOODLED PRO IP
LED quantity:	6 LEDs (1 W each). (12R+12G+12B).
Beam angle:	25°.
Operating modes:	DMX/Auto/Master-Slave.
DMX channels:	6.
Flash ratio:	1-8 flash p/s.
IP range:	IP 65.
Power consumption:	54 W.
Main supply:	AC 110-240 V, 50-60 Hz.
Dimensions:	465 x 375 x 400 mm.
Weight:	7.5 kg.

Thanks to its IP range (IP 65), this projector of 36 high intensity LEDs (1W each, 12 for each primary colour) is perfectly appropriate for outdoor and indoor installations.

Its beam angle is particularly useful to "paint" large areas and to use it like floodlight thanks to its beam width. It features several operating modes (DMX, Audio, Master/Slave, etc.) easily accessible through the rear panel interface.




FLOODLED PRO 45

144W RGB LED projector

NEW

DMX



FLOODLED PRO 45 is a lighting effect with RGB LED technology that creates many effects thanks to its different operating modes.

Aluminium housing and front crystal cover provides resistance to the fixture. Due to its form, there is no problem to integrate it on stages (mobile applications, theatres, etc.).

It features 45 LEDs (15 R, 15G, 15B), each one with WASH type lens that scatters the colour and provides a natural and uniform chromatic tone.

DMX control of the fixture depends on operating mode:

- 1 channel: selection of one colour from the 36 variations.
- 2 channels: macro selection and brightness.
- 3 channels: individualized control of RGB colours.
- 7 channels: Mix of the previous operating modes + strobe and Master control.

In addition to DMX modes, **FLOODLED PRO 45** can operate in audio mode (audio synchronization) or with one of the six preset programs. Rear interface shows the operation mode in action and features buttons to change modes.

TECHNICAL DATA	FLOODLED PRO 45
LED quantity:	45 LEDs (15R+15G+15B)
DMX channels:	1,2,3,7 (depending on operating mode).
Main supply:	AC 100-240 V, 47-63 Hz
Power consumption:	61 W (AC 230 V).
Dimensions:	340 x 196 x 160 mm.
Weight:	4.6 kg.

	0.5m	1m	1.5m	2m	2.5m	3m	4m	5m	
RED	5190	1930	910	500	324	229	129	88	LUX
GREEN	7710	2960	1420	760	504	357	200	137	LUX
BLUE	540	200	90	50	35	25	15	10	LUX
WHITE	13420	5070	2320	1320	854	607	342	235	LUX
L x W	L: 0.492 W: 0.392	m.							



SUPERBLINDLED 4 IP

65
IP

144 W RGB LED projector



NEW



DMX

TECHNICAL DATA	SUPERBLINDLED 4 IP
LED quantity:	4 x 36 (1W each), (12R+12G+12B).
Beam angle:	15°.
Operating modes:	DMX/Auto/Master-Slave.
DMX channels:	7.
Flash ratio:	1-8 flash p/s.
IP range:	IP 65.
Power consumption:	162 W.
Main supply:	AC 110-240 V 50-60 Hz.
Dimensions:	440 x 440 x 265 mm.
Weight:	12 kg.

This projector is adequate to outdoor installations due to its elevate IP range (IP 65). It features 4 independent blinder spots with 36 high intensity LEDs (1W each, total 144 LEDs).

Its beam angle is particularly appropriate for large lighting areas and for live shows.

It includes 3 operating modes (DMX, Auto, Master/Slave) easily accessible from the rear panel interface.

NEW

TL 9 LED

RGB LED truss illuminator

TL 9 LED is a truss illuminator with functions like colour-change and RGB colour mixing. It features 1W LEDs and, thanks to its display and its access buttons, it results very easy to edit the different operating modes.


There are 3 operating modes using DMX:

- 3 channels: dimmer control of each primary colour group.
- 5 channels: Master control + strobe function.
- 9 channels: LED distribution in 3 groups + dimmer individualized control.


TL 9 LED also provides an audio synchronization mode with colour patterns and speed adjustment. A manual configuration is possible for dimmer level of each colour: this is particularly appropriate for permanent light effects.



DMX



TECHNICAL DATA	TL 9 LED
DMX channels:	3 modes (3, 5, 9 channels).
LED quantity:	9 LEDs (1 W each / 2R, 3G, 3B).
Lifetime:	50.000 h.
Wave length:	1343 R, 3430 G, 253 B, 4830 Wh @ 1m.
Main supply:	AC 230 V 50 Hz.
Dimensions (WxHxD):	270 x 220 x 310 mm.
Weight:	2.3 kg.





SuperParLED 3610 IP

RGB LED projector

65
IP

NEW



DMX

This projector is adequate to outdoor installations due to its elevated IP range (IP 65). Its reduced beam angle makes it particularly appropriate for light intensity focus, avoiding light dispersion.

It features 36 high intensity LEDs (1 W each, 12R, 12G, 12B), and includes operating modes (DMX, Auto, Master/Slave) easily accessible from the rear panel interface.

With the double-handling system, **SUPERPARLED 3610 IP** easily integrates itself on trusses, floors and walls.



TECHNICAL DATA	SUPERPARLED 3610 IP
LED quantity:	36 LEDs of 1W each (12R, 12G, 12B).
Beam angle:	15°.
Operating modes:	DMX/Auto/Master-Slave.
DMX channels:	6.
Flash ratio:	1-8 flash p/s.
IP range:	IP 65.
Power consumption:	54 W.
Main supply:	AC 110-240 V 50-60 Hz.
Dimensions:	350 x 285 x 275 mm.
Weight:	4 kg.

RGB LED

54^W LED PROJECTOR

PARLED PRO 64

54W RGB LED projector

This range of projectors featuring 18 LEDs (3 W each) include the three RGB colours in the same LED, creating colour mixing from a unique point to achieve optimum colour definition.

All the electronic for control has been inserted in a conventional PAR 64 spot so they can be integrated in any installations using PAR spots. Contrary to conventional spots, there is no need to change filters.

DMX control of these fixtures depends on selected operating mode (36 variations, macro selection, brightness configuration, individualized RGB control, mix of previous modes, strobe control and master control). These projectors can also operate in audio modes, using one of the 6 preset programs.

TECHNICAL DATA	PARLED PRO 64/IP
LED quantity:	18 RGB (3 in 1).
Individual LED consumption:	3 W each one.
DMX channels:	1,2,3,7 (depending on operating mode).
Main supply:	AC 100-240 V, 47-63 Hz.
Power consumption:	62 W (AC 230 V).
Dimensions:	PARLED PRO 64: 472 x 276 x 266 mm. PARLED PRO 64 IP: 265 x 333 x 296 mm.
Weight:	PARLED PRO 64: 4.1 kg. PARLED PRO 64 IP: 7.1 kg.




NEW

DMX

65
IP

PARLED PRO 64 IP

RGB LED projector for outdoor applications



	0.5m	1m	1.5m	2m	2.5m	3m	4m	5m	
RED	1860	1000	350	200	140	110	60	50	LUX
GREEN	1350	390	210	130	90	60	40	30	LUX
BLUE	48	13.7	8.8	4.7	3.6	2.9	2.2	1.4	LUX
WHITE	2620	1390	730	420	300	200	120	90	LUX
∅	0.401	0.623	0.845	1.066	1.288	1.510	1.953	2.396	m



NEW

DMX

LED FIXTURES



Serie MULTIPAR LED

RGB and WHITE LED projectors

MULTIPAR LED 1W Colour features 24 LEDs (1 W each) divided in RGB colours (8R, 8G, 8B). It can be manually controlled or using DMX signal, though its four control channels. DMX start address can be configured by DIP switches.

Its internal memory includes preset programs that can be triggered in automatic or audio modes. It is so easy to use that it can be controlled without lighting console.

TECHNICAL DATA	MULTIPAR LED 1W Colour
Operating modes:	DMX, Auto, Manual and Audio (internal microphone).
DMX channels:	7.
Power consumption:	30 W.
Main supply:	AC 220V 50 Hz.
Dimensions (WxHxD):	210 x 210 x 130 mm.
Weight:	3 kg.



DMX

MULTIPAR LED 1W Colour

MULTIPAR LED 1W WHITE features 24 white LEDs that provide high luminosity for a perfect integration in conventional lighting installations using Multipar. Its internal memory includes preset programs that can be triggered in automatic or audio modes. It is so easy to use that it can be controlled without lighting console.

TECHNICAL DATA	MULTIPAR LED 1W WHITE
Operating modes:	DMX, Auto, Manual and Audio (internal microphone).
DMX channels:	3.
Power consumption:	30 W.
Main supply:	AC 220V 50 Hz.
Dimensions (WxHxD):	210 x 210 x 130 mm.
Weight:	3 kg.



DMX

MULTIPAR LED 1W WHITE

MULTIPAR LED is a projector featuring 150 LEDs in a MULTIPAR. All the electronic for control has been inserted in a conventional PAR 64 spot so they can be integrated in any installations using PAR spots.

Different operating modes are available to control this fixture: automatic mix with speed selection, audio synchronization or DMX signal. For the latter, **MULTIPAR LED** uses 6 channels: 3 for individual control of R,G,B colours and 3 others for preset colour macro selection, strobe effects and automatic modes.

TECHNICAL DATA	MULTIPAR LED
Operating modes:	DMX, Auto, Manual and Audio (internal microphone).
DMX channels:	6.
Power consumption:	20 W.
Main supply:	AC 220V 50 Hz.
Dimensions (WxHxD):	210 x 210 x 130 mm.
Weight:	2.5 kg.



DMX

MULTIPAR LED

MINIMULTIPARLED 121

RGB LED projector



DMX

MINIMULTIPARLED 121 is a projector that includes high efficiency LEDs (1 W each) with colour-change and RGB colour-mixing functions.

Thanks to its dimensions and because there is no heat emission, it can be easily integrated in stores, booths or expositions to highlight exhibited products.

Different operating modes are available to increase possibilities for effects. Thus, DMX control mode includes 6 operating modes: preset colour macro selection (36 available), independent control of primary colour groups and final mix, strobe effects with speed adjustment, audio synchronization (6 internal programs with speed control) and control of 7 colour pattern trigger speed (loop mode).

TECHNICAL DATA	MINIMULTIPARLED 121
DMX channels:	6 modes (1, 2, 3, 4, 6, 7 channels).
LED quantity:	12 LEDs (4 R, 4 G, 4 B).
Lifetime:	50.000 hours.
Main supply:	AC 230 V 50 Hz.
Power consumption:	21 W.
Dimensions:	250 x 185 x 140 mm.
Weight:	2.4 kg.



MODEL	PAGE
-------	------

Symbols

12/24V POWER SUPPLY 87

A

APU 604 75
 APU 605 75
 AR 32 18
 AR 6 21
 ARCDIM 610 DMX 33
 AR PS1 20
 AR RGB 20

B

BAR 4150 DMX 63
 BAR 6200 DMX 63
 BPD 161 E 62
 BPD 161 5C 62
 BPD 262 E 62
 BPD 262 5C 62
 BPD 661 62
 BPD 662 62

C

C 72 DMX 49

D

D 40 K2 28
 D 66 K2 28
 D 66 K3 26
 DECOLED CONTROLLER 80
 DECOLED RGB 80
 DECOLED WHITE 3K 80
 DECOLED WHITE 6K 80
 DMX-NET 48 44
 DMX-NET 8 44
 DMX ANALYZER 51
 DMX PATCHER 47
 DMX PLAYER 5 40
 DMX RECORDER 41
 DMX RECORDER 19" 41
 DUODIM 34

E

ESD 10 K 55
 ESD 5 K/2 54
 EST 1 K 53
 EST 2 K 53
 EST 500 53
 EST 519/2 54

F

FLOODLED PRO 45 93
 FLOODLED PRO IP 92
 FS 4 DMX 49

G

GALAXY DMX 8

H

HOMEDIM 23
 HOMELED 22

I

IS 2 46
 IS 6 46

J

JB 2 73

K

KBR 100 91
 KBR 200 91

MODEL	PAGE
-------	------

L

L 16 DMX 17
 L 6 DMX 17
 LD5 RGB 78
 LD SPLITTER 79
 LED LINE 10 77
 LED LINE 200 IP 76
 LED LINE VIDEO 70
 LightON 3 6
 LightON 5 6
 LM-2 45
 LM-3E 43
 LM-3R 43
 LM-4 POWER 84
 LPX 12 DMX 37

M

MERGER DMX 50
 MINIDIM 1 81
 MINIDIM 8(DIN version) 82
 MINIDIM RGB 81
 MINIDIM RGB(DIN version) 82
 MINIMULTIPARLED 121 99
 MULTILED CONTROLLER 83
 MULTIPAR LED 99
 MULTIPAR LED 1W Colour 98
 MULTIPAR LED 1W WHITE 98

N

NC 100 64
 NC 1000 64
 NC 1000 F 64
 NC 100 F 64
 NC 600 64
 NC 800 64
 NEMESIS 136 DMX 9

P

PARLED PRO 64 97
 PARLED PRO 64 IP 97
 PD 61 SC 60
 PD 81 E 60
 PD 81 S 60
 PD 82 E 60
 PD 82 S 60
 POWER SPLITTER 60
 POWER SPLITTER 16 61
 POWER SPLITTER 32 61
 PP CEE 15 63
 PP SCK 6 63
 PROLIGHT 400 DMX 17
 PROLIGHT 6 ANALOG 37
 PUZZLED PCB 74
 PUZZLED PCB PRO VIDEO 68
 PUZZLED PCB VIDEO 68
 PUZZLED PRO 66

S

SCAN 1000 DMX 10
 SCAN 1216 DMX 11
 SCAN 812 DMX 12
 SCANPLAYER II DMX 13
 STAGE 12 P DMX 35
 STAGE 1624 DMX 16
 STAGE 16 DMX 16
 STAGE 2412 DMX 15
 STAGE 4824 DMX 14
 STAGE 4 P ANALOG 36
 STAGE 6P ANALOG 36
 SUPERBLINDLED 4 IP 94
 SuperParLED 3610 IP 96

T

TL 9 LED 95

U

UNIDIM 1 34

MODEL	PAGE
-------	------

V

VIDEO TUBE 72
 VIDEO TUBE DRIVER IP 73
 VIDEO WALL PCB 68
 VMX 4 65
 VT 1200 72
 VT 600 72

W

WBAR 1230 88
 WBAR 1830 88
 WBAR 2430 88
 WD 1512 DMX 25
 WD 2012 DMX 24
 WD 4 SPLITTER & BUFFER 48
 WD 616 KMT 32
 WD 620 DMX 31
 WD 6 SPLITTER & BUFFER 48
 WD 90K DMX 30
 WDP 4 ANALOG 39
 WDP 4 DMX 38
 WDP 8 DMX 39
 WPD 1253-B 56
 WPD 163 58
 WPD 163-B 56
 WPD 323 58
 WPD 323-B 56
 WPD 633 58
 WRN 1230 90
 WRN 1830 90

X

XB-R1 74

MODEL	PAGE
-------	------