

WORK PRO® **W**

NGS Series

Garden Speakers

NGS 80 L

Loudspeaker



WORK PRO presents its new series of garden speakers for low impedance installations. The series consists of the NGS 80 L model with its 2-way system, and NGS 80 S that acts as a subwoofer.

NGS 80 L has been designed to obtain an omnidirectional dispersion of sound, covering a wide area with perfectly integrated elements.

Features

- 2-ways loudspeaker.
- 8" Woofer.
- 1.4" Tweeter.
- Omnidirectional Coverage.
- High IP rate.
- Low impedance configuration



Technical Data	NGS 80 L
LF Transducer	8" Diameter, 1.4" coil
HF Transducer	1.4" Tweeter
Nominal Impedance	8 ohm
Minimum Impedance	6.1 ohm @ 215 Hz
RMS Power	120W
Program Power	240W
Peak Power	480W
Sensitivity (2.38v @ 1m)	85dB SPL
Peak SPL	112dB SPL
Frequency Range (Full Space)	53Hz/90Hz @ 22kHz with recommended presets
Recommended High Pass Filter (Standalone)	Butterwoth 24dB/Oct, 50Hz
Recommended High Pass Filter (With NGS80S)	Butterwoth 24dB/Oct, 120Hz
Coverage (-6dB)	360°
Dimensions:	ø 340 x 400 mm
Weight:	4.4 kg

NGS 80 S

Subwoofer))))

NGS 80 S is the subwoofer of this series of garden speakers and can be used as a bass boost in combination with the NGS 80 L.

Being of identical shape and colour to the NGS 80 L model, its discreet integration in any environment is assured, allowing to acclimate large outdoor spaces taking advantage of its high IP rate and omnidirectional dispersion.

Features

- 8" Woofer.
- Omnidirectional Coverage.
- High IP rate.
- Low impedance configuration



Technical Data	NGS 80 S
LF Transducer	8" Diameter, 2" coil
Nominal Impedance	8 ohm
Minimum Impedance	7.3 ohm @ 143 Hz
RMS Power	350W
Program Power	700W
Peak Power	1400W
Sensitivity (2.38v @ 1m)	83dB SPL
Peak SPL	114.5dB SPL
Frequency Range (Full Space)	35Hz @ 145Hz/185H with recommended presets for NGS 80 L
Recommended High Pass Filter	Butterwoth 24dB/Oct, 25Hz
Recommended Low Pass Filter	Butterwoth 24dB/Oct, 100Hz
Coverage (-6dB)	360°
Dimensions:	ø 340 x 400 mm
Weight:	6.4 kg



WORK PRO® **W**



Av. del Saler, nº 14 · Pol. Ind. L'Alteró · Silla 46460 · Valencia · Spain · Phone: +34 96 121 63 01
equipson@equipson.es

Due to a policy of ensuring constant improvement, Equipson S.A. reserves the right to change the specification in materials or designs of any product supplied without notice.